

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Delray

TECHNICAL CHARACTERISTICS

Available Formats:	32x32, 24x24, 12x24, 2x4 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	32x32(10), 24x24(10), 12x24(20)
Thickness in mm:	11mm / 10mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte and Polished
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	>.42 (Matte Only)
Scratch Hardness (MOHS)	5-6 class	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	20.67	Pieces per Carton:	3
SqFt per Pallet:	578.76	Pounds per Carton:	103.56
Boxes per Pallet:	28	SqFt per Container:	8102.60
Pallets per Container:	14		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".