

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Sherwood

## TECHNICAL CHARACTERISTICS

Available Formats:	6x32		
Style Description:	Wood Plank	Glaze Application Method:	H.D.I.T. Porcelain
Visual Characteristics:		Number of Faces/Screens:	30
Thickness in mm:	10mm	Number of Punches/Molds:	4
Modular Suitability:		Body Type:	Porcelain
Application:		Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:	No	Recommended Grout Joint:	>2mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.2%	Static COF:	Wet 0.77 , Dry 0.81
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	>50N/mm <sup>2</sup>
Frost Resistant:		Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GLA		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	9
SqFt per Pallet:	558.24	Pounds per Carton:	53.96
Boxes per Pallet:	48	SqFt per Container:	10,048.32
Pallets per Container:	18		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".