

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Taj Mahal

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 12x24, 3x24 Floor Bullnose, 2x2 Mosaic 12x12 Sheet		
Style Description:	Matte and Polished	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	24x24 (32), 12x24 (16)
Thickness in mm:	10.5mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	16% pre-consumer	Surface Type:	Matte and Polished
Rectified:	Yes	Recommended Grout Joint:	3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	-0.30%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	Polished >0.42, Matte 0.43
Scratch Hardness (MOHS)		Breaking Strength:	+9*10 <sup>6</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	P: GA, M: GA/GLA, GLB-GHB, GLA-GHA		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	3
SqFt per Pallet:	465.20	Pounds per Carton:	55.71
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".