

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**Natura Wood**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x48, 8x48		
Style Description:		Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Wood plank	Number of Faces/Screens:	12
Thickness in mm:	11.5mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:		Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.06	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	<0.42
Scratch Hardness (MOHS)		Breaking Strength:	3195
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	GA(V)		

## PACKING INFORMATION - 8x48 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	10.33	Pieces per Carton:	4
SqFt per Pallet:	444.19	Pounds per Carton:	51.13
Boxes per Pallet:	43	SqFt per Container:	9772.18
Pallets per Container:	22		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".