

A Industrial Adhesives & Tapes

Products | Applications | Industries | Capabilities | Support

<u>United States</u> > <u>All 3M Products</u> > <u>Market Segments</u> > <u>Manufacturing and Industry</u> > <u>Industrial Adhesives & Tapes</u> > <u>3M Tapes & 3M Adhesives</u> > <u>Sealants</u> > <u>3M™ Polyurethane Adhesive Sealant 550 Fast Cure</u>

3M™ Polyurethane Adhesive Sealant 550 Fast Cure

3M Product Number 550



3M[™] Polyurethane Adhesive Sealant 550 FC is a fast curing polyurethane designed to seal and bond many substrates in a wide variety of applications.

- · Paintable multi-purpose adhesive sealant
- · Above and below waterline
- · 60 minute skin time

Overview Documents

Provides excellent adhesion to concrete, wood, aluminum, most lacquered metals, polyester, glass, stone and many other substrates.

Specifications

Application Method	Hand or pressure caulk
Brand	3M
Capabilities	Sustainability
Color	Gray, White, Black
Consistency	Medium paste
Consumer Label	No
Container Volume	5 Gallon
Cure Rate	>4 mm/24 hr
Elongation	>600 Percent
Hardness	45 Shore A
Industries	General Industrial, Construction, Marine, Specialty Vehicle Transportation
Modulus at 100%	87 Pound-Force Per Square Inch
Product Form	Gallon
Skin Time	50 - 90 Minute
Solids Weight Percent (Approximate)	90 Percent
Tack Free Time	1 Hour
Tensile Strength	300 psi
Volatile Organic Compounds (VOCs)	29 Grams Per Litre

3M: News | Careers | Investor Relations | MSDS Search | Transport Information Search | Contact 3M