



GENESIS™

THE EVOLUTION OF ADHESION

A High Performance Primer/Sealer Formulated For Use With All Types Of Sealcoatings



Oil Spot Primer/Sealer

Fast dry times, ready to accept sealer in as little as 30 Min. Excellent hiding properties, can be used as a black-out paint for old traffic markings. Excellent for use as a stand alone sealer on asphalt or concrete.


Adhesion Promoting

State of the art formulation bonds to the most difficult petro-chemical contaminants. Recommended for smooth polished pavement aggregates and new asphalt patches.



America's Best Performing Sealcoating Primers, Additives and Pavement Protection Products

Get The Star-Seal Contractors Resource Smartphone App Today!



14041 Chrisman Rd. ▲ Houston, TX 77039

281-442-0050

www.lonestarsealcoat.com



GENESIS™

THE EVOLUTION OF ADHESION

Specialty Primer/Coating For Oil Spots, Grease Contaminations, Polished Aggregates, Fresh Asphalts and Problematic Adhesions Areas

GENERAL DESCRIPTION

STAR® GENESIS™ A new generation of high performance, adhesion promoting primers that are offered to serve a diverse set of needs in an evolving sealcoating industry. STAR® GENESIS™ is a water based, 100% acrylic polymer coating that is fortified with specialty chemicals to promote adhesion to problematic areas in both asphalt and concrete pavements. STAR® GENESIS™ is the FIRST product you should look to when you encounter a challenging adhesion situation over problematic surfaces that need to be sealcoated. STAR® GENESIS™ overcomes the common problems faced every day when working to cover surfaces that have been contaminated by oils, grease, fats, tree sap deposits, fuel spillage and anti-freeze drippings. Also highly effective in priming aged pavements and polished aggregates, freshly patched asphalt areas and concrete pavements that are difficult for sealcoatings to adhere to.

OUTSTANDING PROPERTIES

- As a Coating - will prevent oil, grease and contaminants from penetrating into the asphalt pavement.
- As a Primer - will prevent oil, grease and contaminants from bleeding up through the sealcoating, and will improve surface appearance.
- STAR® GENESIS™ will effectively stop, or greatly reduce, tile and carpet staining which is sometimes caused by tracking sealcoatings by foot into stores and businesses. Apply a finishing coat of STAR® GENESIS™ along the entire width, and preferably out to a 50 foot depth, in front of the building entrances at full strength, without dilution.
- On Concrete - will aggressively adhere to concrete surfaces and act like a sealcoating by itself or as a primer so that sealcoating appears uniform across all surfaces on a property with both concrete and asphalt pavements.
- Will eliminate the need for excessive surface preparation that could damage the asphalt substrate.
- Is easy to use straight from the container. Minimal on-the-job mixing.
- Dries to rich black satin finish in 30 minutes, Cures in 2 to 4 hours.
- Useful as a black out paint for old traffic control markings.

RECOMMENDED USES

STAR® GENESIS™ is excellent where concrete and asphalt are used together and a uniform appearance is desired, for example; drive through lanes or gas station fueling pads. Recommended on all asphalt surfaces where contamination and oil spotting or black out is needed and problems need to be treated prior to sealcoating application. Excellent for priming aged asphalt aggregate that is polished due to tire abrasion, allowing sealcoating to adhere more tenaciously than unprimed surfaces.

MIX DESIGN RECOMMENDATIONS

STAR® GENESIS™ IS SUPPLIED READY TO USE.

There is no dilution necessary. In unusually hot conditions clean potable water, at a maximum of 5% by volume, can be used to reduce STAR® GENESIS™

APPLICATION RATES

Must be applied to structurally sound pavements. Do not apply over chip seal or gilsonite sealed surfaces.

Apply One Coating of STAR® GENESIS™ as a primer over the contaminated area - the total coverage rate of 125 - 150 Sq. Ft./Gal. (3.0 - 3.7 Sq. Meter/Liter).

IMPORTANT WEATHER LIMITATIONS

- Surface and air temperature should be a min. 50° F (10° C) and rising.
- Do not apply on rainy, foggy, or extremely humid days, or when rain is in the forecast within 24 hours.

SURFACE PREPARATION

For best results remove all loose dirt and scrape off any heavy built up oil and grease. Hose off with clean water and let dry. Fresh oil drippings and contaminations must be washed with a detergent and then properly dried.

APPLICATION TOOLS

- Use conventional tools; Brush, roller, rubber squeegee or low pressure sprayer.
- Clean up with water. Do not discard washings in the bodies of water or down sewer drains.
- Dried primer on tools - Wire brushing, scarping and peeling.
- Keep stored containers sealed tightly.

CURING TIME

Cure time will vary according to temperature and humidity at the time of application. Insufficiently cured films wear prematurely. Lower temperatures, high humidity and lack of direct sunlight will prolong the cure time. Higher temperatures, lower humidity and direct sunlight accelerate the cure process. After the application of STAR® GENESIS™ the coating should dry in approximately 30 minutes and fully cure in 2-4 hours in good conditions.

CAUTIONS

KEEP FROM FREEZING / KEEP OUT OF REACH OF CHILDREN

May cause skin irritation. Wear gloves and protective clothing. In case of contact, flush skin or eyes immediately with fresh water. If the product gets in the mouth or eyes see a physician immediately. Consult a Safety Data Sheet for details.

PACKAGING & AVAILABILITY

5-Gallon plastic pails, 55-gallon drums & 275-gallon plastic totes, and bulk at all STAR plant locations.

WARRANTY & DISCLAIMER The suggestions and related data contained on these pages are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. S.T.A.R., Inc. will not be responsible for any indirect or consequential damages. We will either replace or refund the purchase price in the event the products are proved to be defective, at our option.



STAR
SPECIALTY TECHNOLOGY AND RESEARCH

WORLD-WIDE HEADQUARTERS
1150 Milepost Drive, Columbus, OH 43228
+1-800-759-1912 • www.starseal.com