

4184 E. Conant St. Long Beach, CA 90808 Tel. 888-900-1002 Fax. 310-900-1088 www.turboairinc.net

Project :	
Model #:	
Item #:	Qty:
Approval :	

Condensing Unit

Model: TS020XR404A3





___FEATURES / BENEFITS =__

- Blue anti-corrosion-fin increases the life span of the coil.
- Seamless inner groove copper tube increases the heat exchange rate by reducing the space between the fin and copper tube.
- Highest quality compressor in the world.



- Head pressure control stabilizes the freezing of liquid line, minimizes formation of flash gas to increase efficiency of the system, and prevents compressor damage by controlling high pressure.
- Experienced engineers have designed the system for maximum sfficiency.
- Fan Blades : Specifically matched with motors and coil for maximum air movement and cooling.

- Control box is designed for easy installation.
- Low pressure control is adjustable.
- All the parts are compliant with industry standards and interchangeale with readily available parts.
- Wiring: Easily accessible. Compressor comes with a wiring harness that is manufactured with connections that will not come loose with vibration.
- Control box and service valves are located outside for easy service.
- Base : Heavy duty steel. Legs are 2-1/6" tall
- Cabinet: Prepainted with galvanized body. Protects against corrosion.
- All products carry UL, cUL, ISO 9001 approvals.





Condensing Unit

Model: TSO20XR404A3

PERFORMANCE CHART

	0°F(SST)	-10°F	-20°F	-25°F	-30°F	-35°F	-40°F
90'F(AMBIENT)	11970	9920	8010	7130	6310	5600	4900
95'F	11510	9540	7700	6860	6070	5390	4710
100'F	11050	9160	7390	6590	5830	5170	4520
110'F	10130	8400	6780	6040	5340	4740	4140


SPECIFICATION


Compressor	ZF06K4E-TF5	
Line Size	1/2" Liquid 7/8" Suction	
Receiver 90%	13	
Fan Data	2Fan (2010CFM)	
Dimensions	28.27(D) x 38.5W) x 22.87(H)	
Net Weight	256 Lbs	
Power Supply	208-230/3ph/60hz	
Compressor Amp	8.3	
MCA	11.3	
MOPD	15	

Design and specifications subject to change without notice

- Suction and discharge vibration eliminators with Discus compressors.
- Oil failure switch with Discus compressors.
- To prevent damage of compressor that resulted from liquid-compression, accumulator was installed in this units.
- To improve efficiency, installed oil separator
- WARRANTY: 1 Year Compressor Warranty (4 Year extended warranty available)
 1 Year Fan Motor and Parts Warranty

PLAN VIEW (unit: inch)







■ **Toll Free**: 888-900-1002









