



# Campbell-Mack Supply (1985) Ltd.



## Shackles

### G209 SCREW PIN ANCHOR SHACKLE, U.S. TYPE, DROP FORGED HOT DIP GALVANIZED



ITEM NO.	SIZE (INCH)	W.L.L. (TON)	PIN DIA. (INCH)	I.L. (INCH)	N.W. (LBS.)
G209-0316	3/16	1/3	1/4	7/8	0.05
G209-0104	1/4	1/2	5/16	1-1/8	0.12
G209-0516	5/16	3/4	3/8	1-7/32	0.19
G209-0308	3/8	1	7/16	1-7/16	0.31
G209-0716	7/16	1-1/2	1/2	1-11/16	0.38
G209-0102	1/2	2	5/8	1-7/8	0.63
G209-0508	5/8	3-1/4	3/4	2-3/8	1.38
G209-0304	3/4	4-3/4	7/8	2-13/8	2.25
G209-0708	7/8	6-1/2	1	3-5/16	3.38
G209-0100	1	8-1/2	1-1/8	3-3/4	5.32
G209-0118	1-1/8	9-1/2	1-1/4	4-1/4	6.81
G209-0114	1-1/4	12	1-3/8	4-11/16	9.50
G209-0138	1-3/8	13-1/2	1-1/2	5-3/16	13.25
G209-0112	1-1/2	17	1-3/4	5-3/4	17.20
G209-0134	1-3/4	25	2	7	30.38
G209-0200	2	35	2-1/4	7-3/4	45.00
G209-0212	2-1/2	50	2-3/4	10-1/2	85.75

ULTIMATE LOAD IS 6 TIMES THE WORKING LOAD LIMIT.

### G210 SCREW PIN CHAIN SHACKLE, U.S. TYPE, DROP FORGED HOT DIP GALVANIZED



ITEM NO.	SIZE (INCH)	W.L.L. (TON)	PIN DIA. (INCH)	I.L. (INCH)	N.W. (LBS.)
G210-0104	1/4	1/2	5/16	7/8	0.11
G210-0516	5/16	3/4	3/8	1-1/32	0.17
G210-0308	3/8	1	7/16	1-1/4	0.24
G210-0716	7/16	1-1/2	1/2	1-7/16	0.40
G210-0102	1/2	2	5/8	1-5/8	0.59
G210-0508	5/8	3-1/4	3/4	2	1.21
G210-0304	3/4	4-3/4	7/8	2-3/8	2.25
G210-0708	7/8	6-1/2	1	2-13/16	3.16
G210-0100	1	8-1/2	1-1/8	3-3/16	4.47
G210-0118	1-1/8	9-1/2	1-1/4	3-9/16	6.75
G210-0114	1-1/4	12	1-3/8	3-15/16	9.06
G210-0138	1-3/8	13-1/2	1-1/2	4-3/8	11.60
G210-0112	1-1/2	17	1-3/4	4-13/16	15.95
G210-0134	1-3/4	25	2	5-3/4	26.75
G210-0200	2	35	2-1/4	6-3/4	42.31
G210-0212	2-1/2	55	2-3/4	8	71.75

ULTIMATE LOAD IS 6 TIMES THE WORKING LOAD LIMITS