



SPECIFICATIONS FOR EASTPORT 32 SPORTFISH



Base Boat Price \$625,000

LOA:	32 ft 6 inches	Engines:	2 x Volvo D4-300HP
LWL:	31 ft	Top speed:	36 knots
BEAM:	11 ft 6 inches	Cruise:	30 knots
DRAFT:	22 inches	Fuel:	170 Gallons
DISP. (1/2L):	12,500 lbs		

HULL:

- ISO/NPG gelcoat, choice of color with single boot stripe
- Vinylester resin outer skin with multi-axial E-glass laminates and structural foam core
- Solid skin keel centerline and chine's
- Single skin at thru-hulls
- Bilges finished with white gel coat
- PVC guard rail with Stainless Steel rub strip
- Molded quarter guard with Stainless Steel rub strip
- 5 year limited hull warranty

808 Boucher Ave, Annapolis, MD 21403, USA
www.eastportyacht.com Telephone: + 1 410 533 0928



DECK:

- White gelcoat with molded non-skid
- Polyester resin with multi-axial E-glass laminates and foam core
- Molded cockpit hatches with self draining gutters
- High Density core at deck fittings
- Deck bonded to hull with cyano-acrylate adhesive and mechanical fasteners at gunwale
- Polyester/glass/cored hardtop with SS handrails and cable runs for electronics
- Polyurethane painted window frames with opening windows
- Windshield washers
- Glass windows – Tinted
- Clear Eisenglass roll up enclosure for Flybridge
- Stainless Steel deck fittings
- Galley/Bar with SS sink, 110/12v Refrigerator and “Corian” counter-top and storage under
- 1 Dinette with seating for 4
- Sliding cockpit door
- 2 settee berth
- 4” cockpit “Ultraleather” cushions and seat backs
- Todd captains chair
- T top and schedule 40 Aluminum pipe
- Rupp 2 spreader outriggers
- 8 Rod holders behind capatains chair
- Lounge seating for 3 in front of Helm with cusions
- Deck hatch in Cabin top
- Lifting engine hatches
- Deck lockers with gas springs where appropriate
- Stainless steel Bow cleats
- Stainless Steel Bow Chocks
- Stainless steel Spring Cleats
- Stainless Steel Stern Cleats
- Rod holders in aft side decks
- Cup holders at helm and passenger stations



MECHANICAL:

- Twin Volvo D4 300HP Common Rail, fresh water cooled, turbo charged marine diesel engines with 2.43:1 down angle transmission gear.
- 80 amp alternators
- Single lever controls
- Fuel shut offs
- Secondary Fuel filters
- Groco Water strainers
- Aquamet Prop Shafts
- 19" 4 blade Acme propellers in pockets
- Dripless prop shaft seal
- Manganese bronze Struts and cutlass bearings
- Manganese bronze 22 rudders
- 170 gal Aluminum fuel tank with Stainless steel deck fills
- Engine Sound insulation
- Silencer/Mufflers
- Edson stainless wheel
- Teleflex hydraulic steering
- Trim tabs

PLUMBING:

- Rule automatic electric bilge pumps (3)
- Porcelain head with 20 gal holding tank, marina pump out and overboard macerator discharge
- Jabsco Pressure water pump
- Water heater
- 35 gal water tank
- Whale Head Sink and faucet/shower
- Rule Shower sump pump
- Seafit Galley faucet
- Hot/cold Cockpit shower/wash down pump with hose and nozzle
- Bronze seacocks

ELECTRICAL:

- Fully bonded and grounded to ABYC standards
- One group 4D 200 AH house battery and two group 31 105 AH engine starting batteries
- Custom AC and DC electrical distribution panel with battery condition meters
- Tinned copper wiring to inhibit corrosion
- 30 Amp Shore power inlet with 50 ft cable and four 120 amp outlets
- Battery Charger
- Engine compartment lighting
- Navigation and anchoring lights



- Horn
- 7 x cabin lighting
- 2 x reading lights
- Aft deck floodlight
- Courtesy lights
- Recessed cockpit accent lighting
- Cable runs for navigation/stereo/TV and ancillary electronics
- Dash mounted DC outlets

INTERIOR:

- Head with shower, Corian counter, sink, faucet, drains and storage
- V-Berth with filler piece, 4" Sunbrella cushions and storage under
- Sofa seat with 4" cushions
- Hanging locker and storage
- Interior has molded liner with minimum wood trim for easy maintenance and cleaning.
- Shelves above bunks
- CO 2 Detector

Note:

Name brand items subject to change for equivalent item



808 Boucher Ave, Annapolis, MD 21403, USA
www.eastportyacht.com Telephone: + 1 410 533 0928