

The *classic* American line







Classic American line		Retail Price	Weight	Footprint		Firebox		Wood	Load	Heat
				Width	Depth	W	D	Length	per Firing	Output per Firing
Technical Information		USD	lb	in.	in.	in.	in.	in.	lb	Btu
Small Models										
TU1000	4' height, base vent	\$4,990	2,100	33.1	18.9	12.2	9.6	10	17	110,000
TU1000T	5' height, top vent	\$6,290	2,700	33.1	18.9	12.2	9.6	10	21	130,000
TU1450	5' 3" height, base vent	\$7,190	3,000	35.4	18.9	12.2	9.6	10	24	147,000
TU1450T	5' 3" height, top vent	\$7,190	3,100	35.4	18.9	12.2	9.6	10	24	149,000
Mid-Sized Models										
TU2200	5' height, base vent	\$7,990	4,100	40.2	23.6	15.7	14.4	14	32	205,000
TU2200T	5' height, top vent	\$7,990	4,000	40.2	23.6	15.7	14.4	14	32	196,000
TU2200T/51	6' height, top vent	\$8,990	4,600	40.2	23.6	15.7	14.4	14	37	227,000
TLU2000/91	5' 5" height, 15.4" x 18.3" bakeoven, base vent	\$10,990	4,600	36.6	29.5	14.4	12.0	12	37	235,000
TLU2000/93	5' 5" height, 15.4" x 18.3" rear-facing bakeoven, base vent	\$10,990	4,600	36.6	29.5	14.4	12.0	12	37	235,000
Large Models										
TTU2700/4	6' height, top vent	\$10,990	5,700	40.2	29.5	15.7	19.7	16	45	262,000
TTU2700	7' height, see-through firebox, top vent	\$12,990	6,600	40.2	29.5	15.7	24.8	16	52	301,000
TTU2700/75	7' height, 16.5" x 17.1" bakeoven, top vent	\$13,490	6,400	40.2	29.5	15.7	19.7	16	51	295,000
TTU2700/5	7' height, see-through firebox, 16.5" x 17.1" bakeoven, top vent	\$14,990	6,700	40.2	29.5	15.7	24.8	16	54	312,000
TLU2450/1	5' 6" height, 17.7" x 21.9" bakeoven, base vent	\$14,990	6,300	42.5	35.4	15.7	14.4	14	50	295,000
Optional Features (selection)										
TU22Bench	Soapstone two-sided bench for TU2200 (adds 2 3/8" to height)	\$1,265	550	68.5	27.8					
2700/6	Soapstone four-sided bench for TTU2700	\$3,690	1,800	63.8	53.1					
M10L	Tulikivi Classic soapstone tiles, per square foot	\$17	5	11.8	11.8					
5123	Electric elements 2 kW	870	6							

• Retail Price: delivery and on-site assembling are not included. Heat shields, hearth tiles, benches & other accessories are available as optional features

• Weight: Tulikivi heaters are high thermal mass appliances and require appropriate structural support

• Load per Firing : recommended load is 0.8% of the heater's weight. At least 10 hours between firings

• Warranty: 5 years. Tulikivi heaters must be assembled on site by a Tulikivi installer. They are UL/ULC safety tested & listed and don't require EPA certification

• Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise

• Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Those can be reduced to 3" with a Tulikivi specified heat shield

• Floor protection: 3/8" min. thickness of non-combustible material, extending 8" from sides, 8" from back (unless a heat shield is used) and 16" from front of the heater

