

**C**oncealed rough brass flush valve, diaphragm type operation, with 3/4" NPT hand wheel angle stop and back-check. Ships complete with "Kwikfit" threaded union tailpiece, vacuum breaker, spud nut, and elbowed flush tube for 3/4" concealed back spud. All exposed parts are chrome plated. Standard metal oscillating handle.



**Model Shown  
 P571-08-B-T42**

- Maximum Operation Pressure Rating** . . . . .100 PSI (700 KPa)
- Minimum Operation Pressure Rating** . . . . . 10 PSI (70 KPa)
- Water Volume Per Flush** . . . . . 0.9 – 6.8 Gal @ 80 PSI  
 (3.6 – 26.0 L @ 690 KPa)
- Shipping Weight** . . . . . 6.5 lbs (2.9 kg)

**Variations:**

- 01** Wall Thickness from 0" to 1"
- 02** Wall Thickness from 1" to 2"
- 03** Wall Thickness from 2" to 3"
- 04** Wall Thickness from 3" to 4"
- 05** Wall Thickness from 4" to 5"
- 06** Wall Thickness from 5" to 6"
- 07** Wall Thickness from 6" to 7"
- 08** Wall Thickness from 7" to 8"
- B** 1/2" Push Button
- T5** Non-Hold Open Feature
- T42** Sweat Adaptor Kit for Stop

Option "T42" comes standard with the flush valve

