SHEERWEAVE

PORTER PRESTON

Quality Wholesale Window Coverings

Contract • Hospitality • Healthcare • Residential


STYLE 7100

BLACKOUT FABRIC




WEAVING EXCELLENCE WITH INNOVATION


P02 **White**




P04 **White / Bone**




P05 **White / Platinum**




Q05 **Bone**



Q06 **Bone / Platinum**



V21 **Charcoal**



*Colors may vary based on individual computer settings and should only be used for general reference.

Code	Color	SOLAR OPTICAL PROPERTIES TS	RS	AS	TV	SHGC/G VALUE g-tot (glass & blind) *SINGLE* 1/4 CL	*INSULATING* 1 HA
STYLE 7100 - BLACKOUT							
P02	White	0	71	29	0	0.23	0.19
V21	Charcoal	0	71	29	0	0.23	0.19



PROTECTION THAT LIVES ON MICROBAN®

Microban® antimicrobial protection inhibits the growth of stain-causing bacteria, mold and mildew on the shade.

GREENGUARD GOLD

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

APPROVED BY MELANOMA INTERNATIONAL FOUNDATION

MIF Seal of Approval

Safe Use

Halogen Free Flame Retardant

Energy Saving

Printable

TrackLess Technology

Proudly Made In The USA

10 YEAR Interior Warranty

TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorptance
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at www.phifer.com.

STYLE 7100 SPECIFICATIONS

Style 7100 is a durable laminated blackout fabric that combines the woven texture of our Style 2000 as the face fabric with a durable vinyl backing to achieve total light blockage. Style 7100 coordinates easily with other SheerWeave fabrics when multi-purpose shades are needed. All Style 7100 colors have a white backing.

FIRE CLASSIFICATION

NFPA 701 TM#1 (small scale)
NFPA 701 TM#2 (large scale)
NFPA 101 (Class B Rating)
CAN/ULC-S 109 (large and small scale)
IBC Section 803.1.1 (Class B Rating)
BS 5867 Part 2 Type B Performance

Fire classifications are subject to change. Please go to phifer.com for the most current information.

BACTERIA AND FUNGAL RESISTANCE

ASTM E 2180 ASTM G21 AATCC30 Part 3 ASTM D 3273 ASTMG22
GREENGUARD Mold and Bacteria Standard ASTM 6329
Style 2000 face includes Microban antimicrobial additives.

ENVIRONMENTAL CERTIFICATION

GREENGUARD GREENGUARD Gold
Certified to these standards for low chemical emissions into indoor air during product usage

SAFE USE

RoHS/Directive 2002/95/EC REACH (EC 1907/2006) compliant
ANSI/WCMA A 100.1-2007 for lead content
US Consumer Product Safety Commission Section 101

WARRANTY

10-year interior

ACOUSTICAL PERFORMANCE

NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a

UV PROTECTION

Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes

TRACKLESS

Track*Less* Technology minimizes the fiberglass yarns' inherent tendencies to track when being rolled up in a shade. With Track*Less* Technology these same fabrics now track less, roll up straighter and reduce shade fabrication time.

Due to the construction of Style 7100, some cupping may occur.
Railroading this fabric is not recommended

STYLE 7100

WIDTHS

63" and 96"
160 cm and 243.8 cm

ROLL LENGTH

30 Linear Yards
27.4 Linear Meters

COMPOSITION

37% Fiberglass, 63% Vinyl on Fiberglass
Laminated with a two-ply 100% PVC blackout film

MESH WEIGHT

21.6 oz/yd^2
732 g/m^2

FABRIC THICKNESS

0.025 in
0.64 mm

OPENNESS FACTOR

Opaque

ACOUSTICAL VALUE

NRC .05 / SAA .03

PHIFER INCORPORATED
P. O. Box 1700 • Tuscaloosa, Alabama 35403-1700 USA
Phone: 205.345.2120 • FAX: 205.391.0799
Toll Free USA/Canada: 1.800.221.5497
phifer.com • ISO Registered

® SheerWeave is a registered trademark of PHIFER INCORPORATED.
® MICROBAN is a registered trademark of Microban Products Company.
™ UL, the UL logos and the UL mark are trademarks of UL LLC.
Photo courtesy of Rielamericano, Buenos Aires, Argentina.
© PHIFER INCORPORATED V19 021819 3033843