



# RPT-300IV Plus Thermal Printer

## FEATURES

- ✦ Support international languages
- ✦ Easy paper jams clearance
- ✦ Character font size optional
- ✦ Excellent printing quality and reliability
- ✦ Repeated operation and copy printing are possible
- ✦ Easy maintenance for tasks such as head cleaning
- ✦ Built-in interface provides control capability for Cash Drawer
- ✦ Sweet, refused to single leakage phenomenon, so that work better
- ✦ With wall unit, to meet the horizontal, vertical, wall variety of user needs
- ✦ Supported DIP switch setting: easily change cutter, language, speed, print density,
- ✦ Ethernet ports: LAN to achieve printing, sharing resources, easy to manage, flexible
- ✦ A key bomb boot lid, using the Easy paper loading, so goodbye to cumbersome paper loading
- ✦ Board anti-oxidation, dust, moisture, corrosion, effectively extending the life of the machine



## TECHNICAL SPECIFICATIONS:

- |                            |  |
|----------------------------|--|
| ✦ PRINTING METHOD          | : Direct Thermal   |
| ✦ PRINTING SPEED           | : 300 mm/sec   |
| ✦ DOT DENSITY (DPI)        | : 203*180, 180*180   |
| ✦ PRINTING DIRECTION       | : Unidirectional with friction feed  |
| ✦ CHARACTER/LINE           | : Font A (12*24): 48/ 42 columns<br>Font B (9*17): 64/ 56 columns<br>QR Code |
| ✦ PAPER TYPE               | : Thermal paper  |
| ✦ PAPERWIDTH               | : 80mm ± 0.1mm   |
| ✦ PAPER THICKNESS          | : 0.06 ~ 0.09mm  |
| ✦ PAPER ROLL DIAMETER      | : Max. 80 mm   |
| ✦ EFFECTIVE PRINTING WIDTH | : 72mm,576 Dots, 72mm, 512 Dots  |

# RELIABILITY:

- ⊕ TPH LIFE : 100Km
- ⊕ MCBF : 60,000,000Lines
- ⊕ Barcode : EAN-8, EAN-13, CODE 39, CODE 93, CODE 128, ITF , UPC-A, UPC-E, CODABAR, PDF 417, JAN8, JAN13 QR Code
- ⊕ EMULATION : ESC/POS, EPSON EMULATION
- ⊕ SENSOR : Paper end sensor
- ⊕ INTERFACE : Serial + USB
- ⊕ Cash Drawer Port : RJ 11(DC 24 V/1 A)
- ⊕ AUTO CUTTER LIFE : 1,500,000 cuts
- ⊕ PAPER THICKNESS : 0.06 ~ 0.09mm
- ⊕ CUTTING METHOD : Full/Partial Cut
- ⊕ WEIGHT : INCLUDE AUTO CUTTER 1.55 Kg



# POWER:

- ⊕ AC Adapter input : AC220V, 50Hz
- ⊕ AC Adapter output : DC 24V/2.5A
- ⊕ Printer input voltage : DC 24V/2.5A
- ⊕ Operating temperature : 0~45°C Relative
- ⊕ Storage Temperature : 10°C ~ 50°C
- ⊕ Humidity : Operating Humidity 10 ~ 80 %  
Storage Humidity 10 ~ 90 %

