

Waterloo Mfg., Inc.



606 N. Bell Blvd. Cedar Park, Texas 78613

(512) 219-1935 fax (512) 219-7378 e-mail: jcburch@vlmfg.com Web Site: WLMFG.COM

Standard #125 or 200 Series Pocket Door Frame Specifications

All Hardware is genuine "L. E. Johnson Products".

Track Part #100 Aluminum Captive

Track Screws Part # 318440 8-10 X 3/4" Pan Head Phillips

Jamb stiffeners
Jamb Spacers
Part # 1500 Steel "U" Channel
Part # 250061 Heavy Duty Steel
Part # 150063 Heavy Duty Steel

Door Stop Part # 1155 Heavy Duty Steel W/ Rubber cushion

Door Bumper Part # 1513 Rubber W/ 8-18 X 1/2" Round Washer Hd. Screw Part # 1550 Nylon W/ 8-18 X 1/2" Round Washer Hd. Screw

Door Hanger Part # 1120 or #1125 (Depending on series ordered.)

Pocket Frame Construction Specifications;

All Pocket frames are constructed using 1-3/4" X 7/16" Crown Senco or Duo-fast Staples and 1-7/8" hot dipped galvanized nails. Note; more expensive, full 3/4" MDF material is used to construct header and back band to assure that they are straight and to prevent warping after construction! Each Frame is constructed in a special jig designed and built by us to assure that they are straight and square! Each piece of material is hand selected and cut by our staff before construction.

Vertical Back Band 3/4" MDF

Drywall Nailers 1 X 4 White Woods

Header 3/4" MDF

Split Jambs 2x4 wall 3/4" X 1-1/4" F/J Pine Split Jambs 2x6 wall 11/16"X 2" F/J Pine

(CWP Split Jambs are available @ additional cost)

Custom Size Frames are readily available, and we welcome your order.

Thanks,

J. C. Burch President,

Waterloo Mfg., Inc.

page 9