

Farmwood East - Gas Lamp Repair Instructions

Updated: 3-21-2018

Contact:

American Mantle Company
www.americanmantle.us
1-815-942-0864

Order this:

Soft Mantle on Ceramic Ring Gas Wicks
UPC No.: 857299005045
Soft Inverted Mantle #2 /179B Ring (2pcs/pack) for outdoor gaslights @ \$5.75/pack of 2 plus shipping.

Installation Steps:

1. Get your ladder out and go to the gas lamp. Always replace both wicks. Turn off gas supply with flat head screwdriver on collar of lamp. 1/4 or 1/2 turn.
2. Remove all the glass panels and clean with non-abrasive cleanser.
3. Remove and discard thoroughly, the old mantle rings and broken mantles from lamp.
4. Install two new wicks on the two nozzles. One wick on each.
5. Pull the mantle fabric down on each to give the mantle a good bulb-like shape.
6. Replace all but one of the glass panels back on the lamp.
7. Ignite both the mantles on the bottom with lighter or match. **Allow them to burn off completely to ash, with the gas supply off. Do not touch or bump them** or you will put a hole in them, they won't burn correctly if this happens.
8. Turn on the gas supply and ignite both mantles again...leave them burning...replace the last glass panel.
9. Put away your ladder and go have a beer...you are done.
10. Buy a can of black spray paint and paint the whole structure while you are there. Let it dry for 5-10 minutes.

Or....call up Piedmont Gas and have them do it and charge you \$125!

Do not go to Home Depot and buy Coleman Lantern wicks. They don't work.
May the neighborhood shine brightly at night!!