MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Severance Tool Industries Inc. 3790 Orange St

Phone: 989-777-5500 Fax: 989-777-0602

E-Mail: severancetool@sbcglobal.net Website: www.severancetool.com

PO Box 1866

Saginaw MI 48605

TRADE NAME: DOUBLE SIX (M2)

GRADE SPECIFICATION DATE:

OSHA

ACGIH

06/01/2010

MSDS REVISION DATE 02/2001

SEVERANCE TOOL INDUSTRIES INC. Safety Data Sheet

II. HAZARDOUS INGREDIENTS

				PEL		TLV	
MATERIAL OR	COMPONENT	CAS NO.	PERCENT	(Mg/M^{2})		(Mg/M^{3})	
*CHROMIUM		7440-47-3	4.4	1		.50 *	
IRON		1309-37-1	81.0	10.0		5	
MOLYBDENUM	[7439-98-7	5.3	15.0 TOTA	L DUST	10	
		7439-98-7		5.0 RESP. I	FRACT		
*NICKEL		7440-02-0	.4	1.0		1 *	
*VANADIUM		1314-62-1	2.1	0.5 (DUST))	.05 *	
		1314-62-1		0.1 (FUME)		
TUNGSTEN		7440-33-7	6.8	5.0		5	
* REGULATED AS A TOXIC CHEMICAL UNDER SECTION 313, SARA TITLE III AND 40 CFR 372.							
III. PHYSICAL DATA							
BOILING POINT:	≥ 5000 °F		MELTING POINT:		Approximat	ely 2500 °F	
SPECIFIC GRAVITY (H2O=1):	Approx. 7.8-8.2	2 (60 °F)	VAPOR PRESSUR	E:	N/A		
VAPOR DENSITY (AIR=1):	N/A		SOLUBILITY IN H	1 ₂ 0:	Insoluble		
% VOLATILES BY VOLUME:	N/A		EVAPORATION ()	BUTYLACETATE=1):	N/A		
APPEARANCE AND ODOR: Various Shapes, Solid Odorless Metal							
IV. FIRE AND EXPLOSION DATA							
FLASH POINT:	None		FIRE POINT:		None		
V. HEALTH HAZARD INFORMATION							
WE DO NOT CONSIDER THIS PRODUCT IN THE FORM IT IS SOLD TO CONSTITUTE A PHYSICAL HAZARD OR A HEALTH HAZARD. SUBSEQUENT OPERATIONS SUCH AS ABRADING, MELTING, WELDING, CUTTING OR PROCESSING IN ANY OTHER FASHION THAT CAUSES A RELEASE OF DUST OR FUME MAY CAUSE SOME OF THE INGREDIENTS TO CHANGE TO A FORM WHICH COULD AFFECT EXPOSED WORKERS.							
PRIMARY ROUTES OF ENTRY:	I	EMERGENCY FIRS	ST AID:				
Inhalation - Eye Contact - Skin Contact -		Remove to fresh air, if condition continues - consult physician					
Ingestion		Flush well with running water to remove particulate. Get medical attention.					
Brush off excess dust. Wash area well with soap and water.							
		Seek medical help if	f large quantities of m	aterial have been ingested	ł.		
FFFFCTS OF OVEREXPOSI	IRF.						

EFFECTS OF OVEREXPOSURE:

ACUTE: Short term overexposure to the dust, fumes and/or oxides of certain components of steel products may cause irritation of the eyes, nose or throat; or, may result in metal fume fever characterized by a metallic or sweet taste, dryness and irritation of the throat, wheezing, discoloration of the tongue and flu-like symptoms.

REFER TO PAGE 2 FOR THE EFFECTS OF OVEREXPOSURE TO SPECIFIC ELEMENTS.

CHRONIC: Excessive and prolonged overexposure to the dust fumes and/or oxides of certain components of steel products may result in chronic interstital pneumonitis, discoloration of the skin and hair; allergic bronchitis, neoplasms or loss of coordination and balance.

EFFECTS OF OVEREXPOSURE CONT'D.:

ACUTE:

CARBON (C) -- Irritation of eyes and mucous membranes.

MANGANESE (Mn) -- Irritation of eyes, nose, and throat; metallic taste in the mouth; acute pneumonia and pneumonitis (respiratory disease).

IRON (Fe) -- Irritation of eyes, nose and throat; metal fume fever.

CHROMIUM (Cr) -- Irritation of eyes and mucous membranes, dermatitis, skin ulcers and nasal septum perforation.

NICKEL (Ni) -- Irritation of eyes and mucous membranes, dermatitis, "nickel itch", pulmonary edema, asthma, headache and vomiting.

MOLYBDENUM (Mo) -- Irritation of eyes and mucous membranes.

VANADIUM (V) -- As vanadium pentoxide dust or fumes, it may cause irritation of eyes, nose and respiratory tract.

ALUMINUM (Al) -- Possible irritation of eyes and mucous membranes.

COBALT (Co) -- Irritation of eyes and mucous membranes.

COPPER (Cu) -- Irritation of eyes, nose and throat; metal fume fever.

BORON (B) -- Irritation of nose and throat.

TANTALUM (Ta) -- Dust may cause slight irritation to eyes, nose and throat.

TITANIUM (Ti) -- Considered a physiologically inert dust; however, high concentrations may cause irritation of eyes and mucous membranes.

TUNGSTEN (W) -- No adverse health effects have been reported in humans.

CHRONIC:

CARBON (C) -- Irritation of eyes and mucous membranes.

MANGANESE (Mn) -- Inhalation of fumes and dust can cause central nervous system disturbances, increased upper respiratory disorders and infections, cumulative lung damage, psychiatric disorders, liver cirrosis and anemia.

IRON (Fe) -- Inhalation of iron ixide fumes and dust may cause chronic bronchitis, conjunctivitis, choroiditis, retinitis and siderosis of tissues.

CHROMIUM (Cr) -- The toxicity and health hazards of chromium are heavily dependent upon its oxidation state. Trivalent and devalent chromium, as in chromium metal and chromium-containing alloys have a low order of toxicity. The heavvalent form (chromates and chromic acids) may cause irritant and allergic contact dermatitis, skin ulcers and nsasl irritation varying from rhinitis to perforation of the nasal septum. Reported carcinogen.

NICKEL (Ni) -- Nickel dust or fume can cause sensitization dermatitis, "nickel itch", and may cause cancer of the paranasal sinuses and lungs.

MOLYBDENUM (Mo) -- Human industrial poisoning by molybdenum has yet to be reported.

VANADIUM (V) -- As vanadium pentoxide dust or fumes, it may cause irritation of eyes, nose and respiratory tract (More severe than acute exposure), chronic bronchitis and allergic skin rash.

ALUMINUM (Al) -- Possible irritation of eyes and mucous membranes. Reported as a cause of pulmonary fibrosis.

COBALT (Co) -- May cause allergic skin rashes and respiratory disease.

COPPER (Cu) -- Skin irritation; discoloration of the skin or the hair and metal fume fever.

BORON (B) -- Possible irritation of the respiratory tract and nose bleeds.

TANTALUM (Ta) -- Dust may be slight irritant to eyes, nose and throat.

TITANIUM (Ti) -- Considered a physiologically inert dust; however, high concentrations may cause irritation of eyes and mucous membranes.

TUNGSTEN (W) -- No adverse health effects have been reported in humans.

CARCINOGENICITY:

	NTP	IARC MONOGRAPHS	OSHA REGULATED
CHROMIUM (Cr)	YES	YES	YES, PEL established
NICKEL (Ni)	YES	YES	YES, PEL established

VI. REACTIVITY DATA

STABILITY: INCOMPATIBILITY: HAZARDOUS DECOMPOSITION PRODUCTS:

Chemically Stable Reacts with Strong Acids to Generate Hydrogen Gas Metallic Oxides

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF RELEASE OR SPILL: WASTE DISPOSAL METHOD: N/A Solids -- Sale as Scrap

Dust, etc.-- Follow Federal, State and Local Regulations Regarding Disposal.

VIII. SPECIAL PROTECTION INFORMATION

Other Clothing or Equipment:	As required.
Gloves:	As required.
Eye Protection:	Recommended.
	exceeded, provide NIOSH approved respirators.
Respiratory Protection:	If fumes, misting or dust condition occurs and TLV as indicated in Section II is
PERSONAL PROTECTIVE EQUIPMENT:	
VENTILATION REQUREMENTS:	General Recommended. Local As Required.

IX. SPECIAL PRECAUTIONS

USE GOOD HOUSEKEEPING PRACTICES TO PREVENT ACCUMULATIONS OF DUSTS AND TO KEEP AIRBORNE DUST CONCENTRA-TIONS AT A MINUMUM.