



INDUSTRIAL DUCTING

TYPE HW – VENT DUCT

TYPE HW – VENT DUCT

- PVC Coating
- Polyester Base Fabric
- Flame Resistant
- Excellent Breaking & Tear Strength
- Lightweight Material
- Wire Reinforced
- Moisture and Chemical Resistant
- Air Tight & Leak Proof
- Wide Temperature Range
- Available in a Wide Range of Sizes
- Manufactured in Standard 25ft Lengths
- Custom Lengths Available on Request



TECHNICAL DATA

Color	Black, White or Blue
Coating	PVC
Base Fabric	Polyester
Compression Ratio	6:1
Temperature Resistance - Cold	-22° F (-30° C)
Continuous Operating Temperature - Hot	158° F (70° C)
Flame Resistance	UL 94 V-0
Pressure Ratings	Available on Request

SUGGESTED APPLICATIONS

VENT-DUCT is a lightweight PVC coated polyester fabric reinforced with a spring steel wire helix. This product has superior compressibility and flexible characteristics. It is ideally suited for light duty industrial fume extraction. General applications are fume arm extraction, welding, chemical and general fume and dust extraction. The temperature range is -22°F to +158°F (-30°C to + 70°C). The smooth interior results in minimal friction loss and assists in maximizing air flow.