

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

TEOS

TECHNICAL CHARACTERISTICS

Available Formats:	19x19, 12x24, 13x13, 2x2 Mosaic 13x13 Sheet, 3x13 Bullnose		
Style Description:	Breccia-Marfil-Travertino	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Marble Blend	Number of Faces/Screens:	N/A
Thickness in mm:	9.5mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	30%	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	≥ 40/N mm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	Passed
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	GLA/GA		

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.88	Pieces per Carton:	7
SqFt per Pallet:	555.20	Pounds per SqFt:	4.37 Lbs
Boxes per Pallet:	40	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".