



38 METER R-FOLD

NEW MODEL

4 SECTION

BOOM PUMP



JXLR 38-4.16*

BOOM SPECIFICATIONS

Vertical Reach	37.1 m (121'9")
Horizontal Reach	33.1 m (108'7")
Reach from Front - Cabover	30.3 m (99'5")
Unfolding Height	8.6 m (28'3")
1st Section Length	8.7 m (28'7")
2nd Section Length	7.89 m (25'11")
3rd Section Length	8.08 m (26'6")
4th Section Length	8.43 m (27'8")
Outrigger	X - Style
Front Spread	6.2 m (20'4")
Rear Spread	7.1 m (23'4")

GENERAL SPECIFICATIONS

Pipe Size (ID)	125 mm (5")
Boom Control Valve	Proportional (by HAWE)
Radio Remote	Dual Wireless Transmitter System
Vibrator	Standard
Water Pump	Hydraulic Power 20 bar (290 psi)
Water Tank	800 L (211 G)
Wear Parts	Carbide
Popular Upgrades [†]	LED Boom Light Kit LED Outrigger Lights Heated Water Tank Air-Cuff Twin Wall Pipe 18 cell Pump Kit Big Mouth S-Tube

[†]more options available, ask your sales rep for details.

PUMP SPECIFICATIONS

Output	Rod Side	164 m ³ /h (215 yd ³ /h)
	Piston Side	102 m ³ /h (133 yd ³ /h)
Pressure	Rod Side	72 bar (1044 psi)
	Piston Side	115 [†] bar (1668 psi)
Concrete Cylinder Diameter	230 mm (9")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	2100 mm (83")	
S-Tube Size	8" X 7"	
Main Oil Pump	Rexroth Hydromatic A11VSO260	
Hydraulic System Pressure	350 bar (5076 psi)	
Lube System (Hopper)	Automatic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Stokes/Min	31	
Output Control Range	10(13)~164m ³ /(215yd ³ /h)	

[†]Not to be used through boom pipe.

*Contact your sales representative for alternate chassis options.

www.allianceconcretepumps.com



JXLR 38-4.16

BOOM PUMP

1.888.584.7231 1.888.870.0908

Reach from front: 30.3 m (99'5")



DIAGRAMS

