

OUTDOOR

Solar LED Street Light



Aluminium alloy, Radiator and Lamp Shell integrated design
 Easy and safe for installation, 1 year manufacturing warranty, 50,000 hours life over span.
 CE and RoHS

Model	Size (mm)	Solar Panel	Lithium Battery	LED Lamp (with Sensor)	Discharge Time	
					Full Power	Half Power
SYL-AS002-15W	760 x 325 x 140 mm	18V / 25W	12.8V / 10AH	15W Philips	15 hours	30 hours
SYL-AS002-20W	885 x 325 x 140 mm	18V / 35W	12.8V / 18AH	20W Bridgelux	15 hours	30 hours
SYL-AS002-30W	1130 x 325 x 140 mm	18V / 60W	12.8V / 21AH	30W Bridgelux	15 hours	30 hours
SYL-AS002-40W	1130 x 325 x 140 mm	18V / 60W	12.8V / 24AH	40W Bridgelux	15 hours	30 hours
SYL-AS002-50W	1140 x 450 x 140mm	18V / 80W	12.8V / 36AH	50W Bridgelux	15 hours	30 hours
SYL-AS002-60W	1140 x 450 x 140mm	18V / 80W	12.8V / 42AH	60W Bridgelux	15 hours	30 hours
SYL-AS002-80W	1380 x 450 x 140mm	18V / 100W	12.8V / 48AH	80W Bridgelux	15 hours	30 hours

Charge Time: 7 hours

IP (Waterproof Rating): IP65

SEEDS Tech Limited

Room 2, 6/F., Lemmi Centre, 50 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong
www.seeds-life.com