MATERIAL SAFETY DATA SHEET

S-400, 500, 5000 QS, LT, & EZ EPOXY PART A RESIN

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: SUMMITVILLE LABORATORIES, INC. PROPER SHIPPING NAME:

> PO BOX 90 Not Regulated

81 ARBOR ROAD

MINERVA, OH 44657 **UN NUMBER:**

HAZARD CLASS: INFORMATION PHONE: 330-868-6463 **EMERGENCY PHONE:** 330-223-1511 PACKING:

PRODUCT NAME: S-400, 500, 5000 OS, LT, & EZ EPOXY PART A RESIN HMIS INFORMATION:

PRODUCT NUMBER: 52-00-9045A **HEALTH:**

UPC NUMBER:

FLAMMABILITY: PREPARED BY: Safety Manager

REACTIVITY: 0 **DATE PREPARED:** 3/13/00

PROTECTIVE: C

LAST REVISION: 2/15/94

DIGLYCIDYL ETHER OF BISPHENOL A **SYNONYMS:**

2. COMPOSITION/INFORMATION ON INGREDIENTS

CAS# OSHA PEL ACGIH TLV Chemical Name

bisphenol A Diglycidyl Ether Resin 25068386

STYRENE POLYMER 9003536 N/A N/A

ALIPHATIC EPOXIDE 68609961

SILICA, AMORPHOUS, FUMED 7631869 N/A TLV = 2mg/M3 FOR

RESPIRABLE FRACTION OF

1

DUST

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: N/A

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Can cause severe eye irritation. Prolonged exposure may cause permanent damage.

INHALATION: Inhalation by sensitized individual(s) may cause asthmatic symptoms to occur.

INGESTION: May cause severe and permanent damage to mouth, throat, stomach, and digestive tract.

SKIN CONTACT: Prolonged exposure may cause severe irritation including redness and burns.

SIGNS AND SYMPTOMS OF EXPOSURE:

Irritation and/or difficulty breathing, irritation of eyes, skin, mouth and/or nasal passages, possible headache.

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get

medical attention immediately.

INGESTION: If swallowed, drink large amounts of water and induce vomitting. Never give anything by mouth to an

unconscious person. Seek medical attention immediately.

SKIN CONTACT: Wash affected area with soap and water. If irritation persists, get medical attention.

AGGRAVATED MEDICAL CONDITIONS:

Persons with a history of chronic respiratory or skin conditions may be at increased risk of inflamation of their condition from exposure to this product.

SUPPLEMENTAL HEALTH INFORMATION:

This material may cause sensitization from repeated handling without the use of proper protective equipment. Sensitized individuals will have varied allergic reactions to this material or vapors from this material as a life-long, temporary allergic reaction once sensitized.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 300 F FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION: NOT LEL: UEL:

DETERMI

EXTINGUISHING MEDIA: Dry chemical, foam, Co2.

SPECIAL FIRE FIGHTING PROCEDURES:

The use of a positive pressure, SCBA is recommended for firefighters.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known.

COMBUSTION PRODUCTS:

Mixtures of carbon monoxide, carbon monoxide, and other hydrocarbons may be emitted after all water has been driven off, and only dry materials remain, exposed to flame.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Wipe up small spills. Contain and absorb large spills. Dispose of in accordance with Federal, State, and Local regulations, in solids landfill where applicable.

7. HANLDING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from food and drinking water. Keep container closed when not in use.

OTHER PRECAUTIONS:

N/A

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Wear appropriate respirator complying with NIOSH and other appropriate regulations.

VENTILATION:

PROTECTIVE GLOVES:

Impervious gloves and splash aprons recommended.

EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Where splashing is possible, wear protective apron

WORK / HYGENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before smoking, or using the toilet.

ENGINEERING CONTROLS:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

EXPOSURE GUIDELINES:

N/A

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUABILITY IN WATER: Dispersible

APPEARANCE AND ODOR: Off white, milky liquid, slight odor.

BOILING POINT: N/A PERCENT VOLATILE:

VAPOR PRESSURE: N/A PH:

EVAPORATION: N/A MOLECULAR WEIGHT:

POUNDS PER GALLON: VAPOR DENSITY: N/A

SPECIFIC GRAVITY: 1.0-1.2 OTHER PROPERTIES:

MELTING POINT: FREEZING POINT:

10. STABILITY AND REACTIVITY

STABLE:

Stable

INCOMPATIBILITY:

Avoid uncontrolled contamination with Amines, Bases, Mercaptans, and Strong acids.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon dioxides, carbon monoxides, and other hydrocarbons may be released.

HAZARDOUS POLYMERIZATION:

Will Not Occur

11. TOXICOLOGY INFORMATION

Not Available

12. ECOLOGICAL INFORMATION

Keep container closed when not in use. This material may have a desirable odor and taste to anmals and may cause severe injury and/or death to such animals when ingested in this concentrated form.

13. DISPOSAL CONSIDERATIONS

Dispose of in acordance with all Federal, State, and Local regulations.

14. TRANSPORTATION INFORMATION

DOT CLASS: Not Regulated

HAZARD CLASS: UN NUMBER: PACKING:

GUIDE NUMBER:

PROPER SHIPPING NAME: Not Regulated

15. REGULATORY INFORMATION

No information available.

16. OTHER INFORMATON

HMIS INFORMATION: HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PROTECTIVE: C

Disclaimer

The information contained herein is based on the data available to us and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injuries from the use of the product described herein.