

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

NAME	SERIES	Loftwood
------	--------	----------

TECHNICAL CHARACTERISTICS			
Available Formats:	9x48	Glaze Application Method:	HDIT Inkjet
Style Description:	Wood	Number of Faces/Screens:	N/A
Visual Characteristics:	Wood	Number of Punches/Molds:	1
Thickness in mm:	10 mm	Body Type:	Porcelain (<.5%)
Modular Suitability:	No	Color Body Unglazed:	No
Application:	Residential/Commercial	Surface Type:	Matte/Slight Texture
Recycled Content: Post or Pre Customer	N/A	Recommended Grout Joint:	Minimum 3/16"
Rectified:	No		

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	<.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥ .42
Scratch Hardness (MOHS)	N/A	Breaking Strength:	≥ 2600N
Frost Resistant:	Yes	Thermal Shock Resistance:	Passed
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	N/A
Chemical Resistance:	Class A		

PACKING INFORMATION			
SqFt per Carton:	12.06	Pieces per Carton:	4
SqFt per Pallet:	578.88	Pounds per SqFt:	3.98 lbs
Boxes per Pallet:	48	SqFt per Container:	11,577.60
Pallets per Container:	20		

## Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".