

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Tropical

TECHNICAL CHARACTERISTICS

Available Formats:	24x48		
Style Description:	Modern Wood	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Vein Wood	Number of Faces/Screens:	6
Thickness in mm:	10	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	>0.40
Scratch Hardness (MOHS)	5	Breaking Strength:	>35n
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	confirming		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	2
SqFt per Pallet:	325.50	Pounds per Carton:	77.81
Boxes per Pallet:	21	SqFt per Container:	1100.50
Pallets per Container:	31		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".