

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

TEXTURE

## TECHNICAL CHARACTERISTICS

Available Formats:	11x23, 3x3 Mosaic 12x12 Sheet, 3x23 & 3x11 Bullnose		
Style Description:	Fabric like look	Glaze Application Method:	Inkjet
Visual Characteristics:	Wall paer texture	Number of Faces/Screens:	13
Thickness in mm:	9.00 mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	White body
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Flat
Rectified:	No	Recommended Grout Joint:	2 mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	<0.4
Scratch Hardness (MOHS)	3	Breaking Strength:	444.52
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	GLA		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.83	Pieces per Carton:	9.00
SqFt per Pallet:	949.80	Pounds per Carton:	52.39
Boxes per Pallet:	60	SqFt per Container:	14247.00
Pallets per Container:	15		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".