



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	50 %	47.9 kNm	35,400 ft.lbs.
Pump Setting 2	74 %	70.0 kNm	51,630 ft.lbs.
Pump Setting 3	90 %	85.4 kNm	62,920 ft.lbs.
Pump Setting 4	100 %	94.8 kNm	69,923 ft.lbs.

Frequency 37 - 52 blows/min

Related Piston Stroke 3.2 - 1.6 m 10.5 - 5.3 ft.

Maximum batter w/o upper cyl. ext. 1:5 -

with upper cylinder extension 1:1 -

Fuel consumption at full load 10.0 L/hr. 2.64 gal./hr.

Oil consumption 1.0 L/hr. 0.26 gal./hr.

Approx. Weights

Hammer 6110 kg 13,472 lbs.

Piston 3000 kg 6,615 lbs.

Hammer with standard guiding 7210 kg 15,900 lbs.

Capacities

Fuel Tank 67 L 17.7 gal.

Oil Tank 19 L 5.0 gal.

Dimensions

A - Length 5425 mm 17.8 ft.

LH - Length, standard 6490 mm 21.3 ft.

- Length with hydraulic start 6860 mm 22.5 in.

B - Center to trip 445 mm 17.5 in.

B1 - Center to trip with cylinder 610 mm 24.0 in.

C - Center to pump guard 482 mm 19.0 in.

D - Width of hammer 635 mm 24.5 in.

D1 - Width of trip 812 mm 32.0 in.

W - Minimum lead width 660 mm 26.0 in.

*Technical data are subject to change without prior notice

Operating energy based on piston stroke - values are approximate.

Hydraulic start and upper cylinder extension optional.