

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/22/2013 : Version:

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixtures

Trade name : ChemChill Electronic Contact Cleaner 11oz

Product code : 166120

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Follow Label Directions

#### 1.3. Details of the supplier of the safety data sheet

Climate Components, LLC 725 Old Norcross rd. #D Lawrenceville, GA 30045

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification (GHS-US)

Flam. Aerosol 1 H222 Flam. Liq. 2 H225 Acute Tox. 2 (Oral) H300 Eye Dam. 1 H318 Muta. 1B H340 Repr. 1B H360 STOT SE 1 H370 STOT RE 2 H373 Asp. Tox. 1 H304

### 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)

Precautionary statements (GHS-US)



GHS05





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol

H225 - Highly flammable liquid and vapor

H300 - Fatal if swallowed

H304 - May be fatal if swallowed and enters airways

H318 - Causes serious eye damage H340 - May cause genetic defects

H360 - May damage fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

H280 - Contains gas under pressure; may explode if heated

: P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P211 - Do not spray on an open flame or other ignition source

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting/... equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P251 - Pressurized container: Do not pierce or burn, even after use

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash ... thoroughly after handling

P270 - Do no eat, drink or smoke when using this product

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

14/01/2014 EN (English US) 1/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing

P308+P313 - IF exposed or concerned: Get medical advice/attention P310 - Immediately call a POISON CENTER or doctor/physician

P314 - Get medical advice and attention if you feel unwell

P321 - Specific treatment (see ... on this label)

P330 - If swallowed, rinse mouth

P331 - If swallowed, do NOT induce vomiting P370+P378 - In case of fire: Use ... for extinction P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50

P501 - Dispose of contents/container to ...

#### 2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

| Name  | Product identifier  | %           | Classification (GHS-US)  |
|---|---------------------|-------------|--|
| naphtha (petroleum), hydrotreated light       | (CAS No) 64742-49-0 | <= 72       | Flam. Liq. 2, H225<br>Muta. 1B, H340<br>Asp. Tox. 1, H304  |
| 1,1-difluoroethane, liquefied, under pressure | (CAS No) 75-37-6    | 10 - 30     | Liquefied gas, H280  |
| methanol                                      | (CAS No) 67-56-1    | 1 - 5       | Flam. Liq. 2, H225<br>Acute Tox. 1 (Oral), H300<br>Eye Dam. 1, H318<br>Repr. 1B, H360<br>STOT SE 1, H370   |
| n-hexane                                      | (CAS No) 110-54-3   | 1.44 - 2.16 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Repr. 2, H361<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411 |

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician. Specific treatment (see ... on this

label).

First-aid measures after inhalation

Coughing. Remove to fresh air and keep at rest in a position comfortable for breathing.
Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

First-aid measures after skin contact First-aid measures after eye contact

Direct contact with the eyes is likely to be irritating. Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

First-aid measures after ingestion

: Rinse mouth. Do NOT induce vomiting. Fatal if swallowed. Immediately call a POISON CENTER

or doctor/physician. Specific treatment (see ... on this label).

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

Suspected of damaging fertility or the unborn child. May cause genetic defects. May damage

fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation

: Shortness of breath.

Causes serious eye damage.

Symptoms/injuries after eye contact Symptoms/injuries after ingestion

: Fatal if swallowed. May be fatal if swallowed and enters airways.

# 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable gas. Extremely flammable aerosol. Highly flammable liquid and vapor.

14/01/2014 EN (English US) 2/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture.

## 5.3. Advice for firefighters

Firefighting instructions : Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition

sources if safe to do so. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment. DO NOT

fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol level 3.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. No naked lights. No smoking. Isolate from fire, if

possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static

electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Emergency procedures : Ventilate area

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Additional hazards when processed : Flammable gas. Hazardous waste due to potential risk of explosion. Pressurized container: Do

not pierce or burn, even after use. Handle empty containers with care because residual vapors

are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. No naked lights. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Do no eat, drink or smoke when using this product. Wash ... thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/  $\ldots$ 

equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to

temperatures exceeding 50℃/ 122年. Keep in firepro of place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

#### 7.3. Specific end use(s)

Follow Label Directions.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

| methanol (67-56-1) |                  |         |
|--------------------|------------------|---------|
| USA ACGIH          | ACGIH TWA (ppm)  | 200 ppm |
| USA ACGIH          | ACGIH STEL (ppm) | 200 ppm |

14/01/2014 EN (English US) 3/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 8.2. Exposure controls

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. Wear respiratory protection.

Other information : Do not eat, drink or smoke during use.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid.

Color : colorless.

Odor : characteristic.

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available

Melting point : -62 ℃ Lowest Component

Freezing point : No data available

Boiling point : 37  $^{\circ}$  Lowest Component Flash point : <-18  $^{\circ}$  Lowest Component

Self ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : > 760 mm Hg
Relative vapor density at 20 ℃ : No data available

Relative density : 0.69

Solubility : No data available
Log Pow : No data available
Log Kow : No data available

Viscosity, kinematic : 0.83 cSt

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

#### 9.2. Other information

VOC content : 75 %

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Extremely flammable gas. Not established. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition. Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

# 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

14/01/2014 EN (English US) 4/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity : Fatal if swallowed.

| methanol (67-56-1)         |   |
|----------------------------|---|
| LD50 oral rat              | > 5000 mg/kg (1187-2769 mg/kg bodyweight; Rat; Rat) |
| LD50 dermal rabbit         | 15800 mg/kg (Rabbit)                                |
| LC50 inhalation rat (mg/l) | 85 mg/l/4h (Rat)                                    |
| LC50 inhalation rat (ppm)  | 64000 ppm/4h (Rat)                                  |

| 1,1-difluoroethane, liquefied, under pressure (75-37-6) |                    |
|---|--------------------|
| LC50 inhalation rat (mg/l)                              | 176 mg/l/4h (Rat)  |
| LC50 inhalation rat (ppm)                               | 64000 ppm/4h (Rat) |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : May cause genetic defects.Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

| naphtha (petroleum), hydrotreated light (64742-49-0) |   |
|--|---|
| IARC group   | 3   |
| Reproductive toxicity                                | : May damage fertility or the unborn child.Based on available data, the classification criteria are |

Specific target organ toxicity (single exposure) : Causes damage to organs.

Specific target organ toxicity (repeated : May cause dama

exposure)

: May cause damage to organs through prolonged or repeated exposure.Based on available data, the classification criteria are not met

May cause damage to organs through prolonged or repeated exposure

Aspiration hazard : May be fatal if swallowed and enters airways.Based on available data, the classification criteria

are not met

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met. Fatal if swallowed.

Symptoms/injuries after inhalation : Shortness of breath.
Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Fatal if swallowed. May be fatal if swallowed and enters airways.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

| methanol (67-56-1)                        |  |
|---|--|
| LC50 fish 1                               | 15400 mg/l (96 h; Lepomis macrochirus; Lethal)         |
| EC50 Daphnia 1                            | > 10000 mg/l (48 h; Daphnia magna; Lethal)             |
| LC50 fish 2                               | 10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) |
| EC50 Daphnia 2                            | 24500 mg/l (48 h; Daphnia magna)                       |
| Threshold limit other aquatic organisms 1 | 6600 mg/l (16 h; Pseudomonas putida)                   |
| Threshold limit algae 1                   | 530 mg/l (192 h; Microcystis aeruginosa)               |
| Threshold limit algae 2                   | 8000 mg/l (168 h; Scenedesmus quadricauda)             |

# 12.2. Persistence and degradability

| ChemChill Electronic Contact Cleaner 11oz |                  |
|---|------------------|
| Persistence and degradability             | Not established. |

| n-hexane (110-54-3)           |   |
|-------------------------------|---|
| Persistence and degradability | May cause long-term adverse effects in the environment. |

| methanol (67-56-1)              |  |
|---------------------------------|--|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. |
| Biochemical oxygen demand (BOD) | 0.6 - 1.12 g O <sup>2</sup> /g substance                   |
| Chemical oxygen demand (COD)    | 1.42 g O <sup>2</sup> /g substance                         |
| ThOD                            | 1.5 g O <sup>2</sup> /g substance                          |
| BOD (% of ThOD)                 | 0.8 % ThOD   |

| 1,1-difluoroethane, liquefied, under pressure (75-37-6) |   |
|---|---|
| Persistence and degradability                           | Biodegradability in water: no data available. |

14/01/2014 EN (English US) 5/8

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 12.3. Bioaccumulative potential

| ChemChill Electronic Contact Cleaner 11oz |                  |
|---|------------------|
| Bioaccumulative potential                 | Not established. |

## n-hexane (110-54-3)

Bioaccumulative potential Not established.

| methanol (67-56-1)        |  |
|---------------------------|--|
| BCF fish 1                | < 10 (Leuciscus idus)  |
| Log Pow                   | -0.77 (Experimental value; Other, Experimental value; Other) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500).               |

| 1,1-difluoroethane, liquefied, under pressure (75-37-6) |  |
|---|--|
| Log Pow   | 0.75 (Experimental value)                        |
| Bioaccumulative potential                               | Low potential for bioaccumulation (Log Kow < 4). |

## 12.4. Mobility in soil

| methanol (67-56-1) |                  |
|--------------------|------------------|
| Surface tension    | 0.023 N/m (20 ℃) |

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to ...

Additional information : Flammable vapors may accumulate in the container. Handle empty containers with care because

residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

# SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

### 14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosols

flammable, (each not exceeding 1 L capacity)

Department of Transportation (DOT) Hazard

Classes

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

#### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

14/01/2014 EN (English US) 6/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

## SECTION 15: Regulatory information

#### 15.1. US Federal regulations

| ChemChill Electronic Contact Cleaner 11oz |   |
|---|---|
| SARA Section 311/312 Hazard Classes       | Delayed (chronic) health hazard             |
|   | Fire hazard Immediate (acute) health hazard |

#### naphtha (petroleum), hydrotreated light (64742-49-0)

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard
Fire hazard
Immediate (acute) health hazard

#### methanol (67-56-1)

Listed on SARA Section 302 (Specific toxic chemical listings)

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard
Fire hazard
Immediate (acute) health hazard

## 1,1-difluoroethane, liquefied, under pressure (75-37-6)

| ·,· ·································· |   |
|--|---|
| SARA Section 311/312 Hazard Classes    | Fire hazard Sudden release of pressure hazard |
|  |   |
|  | Immediate (acute) health hazard               |

## 15.2. International regulations

### CANADA

| ChemChill Electronic Contact Cleaner 11oz |  |
|---|--|
| WHMIS Classification                      | Class B Division 5 - Flammable Aerosol<br>Class B Division 2 - Flammable Liquid<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| method (C7 EC 4)                          |  |

| nethanol (67-56-1)   |   |
|----------------------|---|
| WHMIS Classification | Class B Division 2 - Flammable Liquid   |
|                      | Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects |
|                      | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects            |
|                      | Class D Division 2 Subdivision B - Toxic material causing other toxic effects                 |

# 1,1-difluoroethane, liquefied, under pressure (75-37-6)

| , , . , , , , , , , , |  |
|-----------------------|--|
| WHMIS Classification  | Class A - Compressed Gas               |
|                       | Class B Division 5 - Flammable Aerosol |

# **EU-Regulations**

No additional information available

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

# Classification according to Directive 67/548/EEC or 1999/45/EC

Carc.Cat.2; R45 Muta.Cat.2; R46 F+; R12 Xn; R20/21/22

Xn; R65 Xn; R68/20/21/22

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

No additional information available

14/01/2014 EN (English US) 7/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 15.3. US State regulations

# 1,1-difluoroethane, liquefied, under pressure (75-37-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List

# **SECTION 16: Other information**

Indication of changes : Revision - See : \*.

Other information : None.

Full text of H-phrases: see section 16:

| At of 11-pillases, see section 16. |   |
|------------------------------------|---|
| Acute Tox. 1 (Oral)                | Acute toxicity (oral) Category 1                                  |
| Acute Tox. 2 (Oral)                | Acute toxicity (oral) Category 2                                  |
| Aquatic Chronic 2                  | Hazardous to the aquatic environment - Chronic Hazard Category 2  |
| Asp. Tox. 1                        | Aspiration hazard Category 1                                      |
| Eye Dam. 1                         | Serious eye damage/eye irritation Category 1                      |
| Flam. Aerosol 1                    | Flammable aerosol Category 1                                      |
| Flam. Liq. 2                       | Flammable liquids Category 2                                      |
| Liquefied gas                      | Gases under pressure Liquefied gas                                |
| Muta. 1B                           | Germ cell mutagenicity Category 1B                                |
| Repr. 1B                           | Reproductive toxicity Category 1B                                 |
| Repr. 2                            | Reproductive toxicity Category 2                                  |
| Skin Irrit. 2                      | skin corrosion/irritation Category 2                              |
| STOT RE 2                          | Specific target organ toxicity (repeated exposure) Category 2     |
| STOT SE 1                          | Specific target organ toxicity (single exposure) Category 1       |
| STOT SE 3                          | Specific target organ toxicity (single exposure) Category 3       |
| H222                               | Extremely flammable aerosol                                       |
| H225                               | Highly flammable liquid and vapor                                 |
| H280                               | Contains gas under pressure; may explode if heated                |
| H300                               | Fatal if swallowed  |
| H304                               | May be fatal if swallowed and enters airways                      |
| H315                               | Causes skin irritation  |
| H318                               | Causes serious eye damage   |
| H336                               | May cause drowsiness or dizziness                                 |
| H340                               | May cause genetic defects   |
| H360                               | May damage fertility or the unborn child                          |
| H361                               | Suspected of damaging fertility or the unborn child               |
| H370                               | Causes damage to organs   |
| H373                               | May cause damage to organs through prolonged or repeated exposure |
| H411                               | Toxic to aquatic life with long lasting effects                   |
|                                    |   |

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt


medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



#### **HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 2 Moderate Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - Technical Chemical

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

14/01/2014 EN (English US) 8/8