

Sundance Window coverings

Vertical Blinds Specifications

Sundance Aluminum Headrail Strap System

Chain and cord control/ wand control

Sundance Track: will be aluminum 6063 T6 alloy and will measure 1 3/4" in width and 1 1/4" in height. The wall thickness of the track is ± 0.040 ". Available in painted ivory.

Carrier: Supporting vane shall have a plastic hook in a low-friction plastic body (3/8"). Carrier shall have polyacetal plastic body and will traverse on rolling self lubricating plastic wheels aligned in the channel runway. Each carrier will contain a self-aligning feature to keep vanes aligned.

Spacing of Louvers: Carriers are attached to each other with a nylon strap. Stems are centered making the headrail reversible. Available in 3 1/8" spacing.

5. Rotation: The louver rotation will be provided by pulling a #6 nickel plated operating chain. Stem rotates 180 degrees. An aluminum 4-prong tilt rod passes through each carrier and imparts rotation to each carrier hook in unison via spur gears. Smooth rotation, with a 3:1 rotation, is provided by a system in a molded plastic control unit. The control unit allows the first vane to hang only 1/2" from the window jam, offering minimal light leakage.

Traversing: Will be by means of a continuous polyester and nylon traverse cord attached to the master carrier and traversing over plastic pulley wheels supported in plastic end caps. Blinds may traverse right to left, left to right, or may be of a split draw, centered, or otherwise specified. The cord will be held down by a weighted cord pulley.

7. Vanes: Can be selected from the Vertical Collection.

Rigid vane material will be suspended from carrier hooks by means of a hole punched in the top of each vane. A bottom chain to be provided, where appropriate.

8. Valances: Optional valances and returns are available in clear front-edged grooved vinyl.

9. Support Brackets: Additional support brackets will be furnished for blinds over 42" in width. Maximum spacing for these brackets are 24".

10. Extension Brackets: Optional.

11. General: The vertical blind shall be free of sharp edges, burrs, or other defects,

Cleaning

A. Clean soiled blind surfaces with a mild soap solution. Do not use steam, hot water, bleach or any abrasive or solvent-based cleaners. Do not wash metallic colors.

B. To ensure proper drying, provide adequate ventilation for blinds.