

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

ERAMOSA

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Stone	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Vein-cut Marble	Number of Faces/Screens:	18
Thickness in mm:	10mm	Number of Punches/Molds:	3
Modular Suitability:	No	Body Type:	Gres Porcelain (.1%- .5%)
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	14%	Surface Type:	Matte/Textured
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	.1%- .5%	Static COF:	Wet: 0.60 Dry: 0.70
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	7	Breaking Strength:	50Nmm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Yes		

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.67	Pieces per Carton:	7
SqFt per Pallet:	546.80	Pounds per Carton:	65
Boxes per Pallet:	40	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".