

201-504-602U

HDMI v1.4 Splitter 1x2, 4Kx2K with Full 3D

The 201-504-602U is an HDMI splitter with two outputs. It distributes the input of the HDMI signal from HD source devices (such as, STB, PC, DVD, HD-DVD, PS3) to two identical output signal simultaneously. In addition, it can be placed at the end of a long HDMI cable to regenerate the HDMI signal.



The resolution of this HDMI splitter can be up to 3840 x 2160 @30Hz and supports full 3D format.

Its video amplifier's bandwidth can be up to 320MHz. This HDMI amplifier splitter is perfectly compatible with HDTV, monitor or projector which is widely utilized on conference room, education building A/V infrastructure.

FEATURES

- Support HDMI 1.4
- Support 3D video format
- Support 8/10/12 bit deep color
- Highest resolution up to 3840x2160@30Hz
- Support highest rate of 3.2G and TMDS clock up to 320MHz
- Supported compressed audio (DTS-HD, Dolby-True HD, DTS, Dolby-AC3, DSD)
- Metal casing design and overall shielding without signal interference
- LED indicates signal and power mode
- Power supply: DC 5V

SPECIFICATIONS

HDMI Signal	HDMI 1.4
HDMI Resolution	Up to 3840x2160@30Hz
Support Video Color Format	8/ 10/ 12 bit deep color
Support Audio Format	DTS-HD/ Dolby-true HD/ DTS/ Dolby-AC3/ DSD
Max Bandwidth	320MHz
Max Baud Rate	3.2Gbps
HDMI Cable Distance	Input cable (1080p <15m, 4K <12m) Output cable (1080p <25m, 4K <15m)
Input Power	Input 100V-240V, 50/60Hz
Output Power	DC5V 1A
Operation Temperature	-15°C to +55°C
Dimensions (L x W x H)	105 x 50 x 20mm
Weight	120g
Accessories Included	DC5V Power Adapter x 1; User Manual x 1

ORDERING INFORMATION

201-504-602U

HDMI v1.4 Splitter, 1x2, 4Kx2K 3D