

CONCRETECH

WB Cure
Water-based curing compound

PRODUCT DESCRIPTION

WB Cure is an emulsion of hydrocarbon resin and aliphatic ketones. WB Cure prevents the rapid evaporation of gauging water that is critical to the proper hydration and strength development of concrete. WB Cure retains over 95% of mixing water for proper strength gain and concrete.

USES

WB Cure is used to chemically cure concrete immediately after finishing operations. WB Cure is economical and is used for curing both interior and exterior concrete structures. WB Cure is available with a green fugitive dye to assist applicators in achieving specified rates of application.

PACKAGING

Available in 18.9 Litre (5 Gallon) pails and 205 Litre (45 Gallon) drums.

LIMITATIONS

WB Cure is a chemical curing compound and will dissipate under normal conditions. WB Cure IS NOT A SEALER OR COATING.

INSTALLATION INSTRUCTIONS

Concrete should be clean and free of all laitance, oil, grease and other foreign substance. Concrete should be free of all standing water prior to applying WB Cure.

Cast, consolidate, level and finish concrete to specification.

Immediately after finishing operations and disappearance of the surface sheen apply WB Cure.

Apply WB Cure by airless sprayer or roller.

SAFETY PRECAUTIONS

Various solvents contain chemicals known to be embryonic toxicants. Consult MSDS for further information.

PROPERTIES

- Economical
- Non-Yellowing
- Versatile
- Will not blush
- Superior bonding characteristics
- Fast Drying

Appearance: Milky white Viscous Liquid
Yield: 300 square feet per gallon (7.34 square meters per litre)

Shelf Life: Approximately 1 year when stored properly
Drying Time: Dries in ½ hour at 25 C

Applicable Standards: Meets or exceeds ASTM C309
Density: 0.905 kilograms per litre (7.5 lbs. per gallon)

TECHNICAL SERVICES

Complete technical information is available from Concretech Inc. and its authorized applicators and distributors. In house laboratory testing is available for specialty applications. Technical services available in North America call toll free 1.888.503.6780

Concretech Inc.'s sole warranty is that our products have been manufactured to meet with our written specifications. The information herein is general information to assist our customers in determining whether our products are suitable for their applications. Our products are intended for sale to commercial and industrial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents, suitability and applications. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent inferred. All patent and trademark rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

CONCRETECH

104, 2567 192 Street
Surrey, BC V3S 3X1

www.concretechproducts.com

Toll Free: 1.888.503.6780
Fax: 1.604.357.1344
Tel: 1.604.210.1147