

5.000" OD, HWDP, WELDED, STANDARD, 6.500" OD x 3.500" ID, NC50 VAM EIS

HEAVY WEIGHT DRILL PIPE BODY

Nominal OD (in)	5.000
Nominal ID (in)	3.000
Pipe Grade	AISI 1340
Heavy Weight Type	STANDARD
HWConstruction	WELDED
Pipe Wall Thickness (in)	1.000
Cross Sectional Area of Pipe Body (in ²)	12.566
Cross Sectional Area OD (in ²)	19.635
Cross Sectional Area ID (in ²)	7.069
Section Modulus (in ³)	10.681
Polar Section Modulus (in ³)	21.363
Torsional Strength (lbs/ft)	66,800
Tensile Strength (lbs)	817,000
Burst Pressure (psi)	26,000
Collapse Pressure (psi)	20,800

HEAVY WEIGHT DRILL PIPE CONNECTION

Tool Joint Grade	VM-65 HW MS
OD (in)	6.500
ID (in)	3.500
Pin Tong Length (in)	27.00
Box Tong Length (in)	21.00
Connection	NC50 VAM EIS
Torsional Strength (lbs/ft)	57,500
Tensile Yield Strength (lbs)	1,020,000
Minimum Make-up Torque (lbs/ft)	26,100
Recommended Make-up Torque (lbs/ft)	32,700
Maximum Make-up Torque (lbs/ft)	34,300
Tool Joint/Drill Pipe Torsional Ratio (New)	0.86
Balanced OD	6.260

HEAVY WEIGHT DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.76
Closed End Displacement (gal/ft)	1.12
Fluid Capacity (gal/ft)	0.37
Drift Size (in)	2.875
Adjusted Weight (lbs/ft)	49.53
Internal Plastic Coating	TK34P
Hardbanding	TCS TITANIUM

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.