

VOLCLAY® CG50

SOIL SEALANT

VOLCLAY® CC-8 CERTIFIED PROPERTIES									
DESCRIPTION	Volclay CG-50 is a natural, granular, high-swelling Wyoming sodium bentonite recommended for lining/sealing applications involving moist soils or those where it is necessary to minimize dust generation.								
APPLICATIONS	Soil/bentonite liners; general sealing applications								
COMPOSITION	Sodium bentonite is a hydrous silicate of alumina primarily consisting of the clay mineral montmorillonite, which swells several times its own volume when wetted.								
FREE SWELL	24 ml/2g minimum (ACC 1010)								
MOISTURE CONTENT	18 ml maximum (API 13A)								
PARTICLE SIZING	12 percent maximum as shipped								
DRY BULK DENSITY	5 percent max. retained on a #10 mesh (2.00 mm) sieve 15 percent max. passing a #200 mesh (75 mm) sieve (ASTM D422)								
PACKAGING	65 lbs/ft ³ (1,040 kg/m ³) typical								
AVAILABILITY	50 lb (22.5 kg) multi-wall paper bags; 2000-lb (900 kg) or 4,000 lb (1,800 kg) super sacks; or bulk.								
APPLICATION INFORMATION	<table border="1"> <thead> <tr> <th>Primary Soil Type</th> <th>Typical Application Rate*</th> </tr> </thead> <tbody> <tr> <td>Sand</td> <td>8-10 lbs/ft² (40-50 kg/m²)</td> </tr> <tr> <td>Silt</td> <td>4-8 lbs/ft² (20-50 kg/m^{2m})</td> </tr> <tr> <td>Clay</td> <td>2-4 lbs/ft² (10-20 kg/m²)</td> </tr> </tbody> </table>	Primary Soil Type	Typical Application Rate*	Sand	8-10 lbs/ft ² (40-50 kg/m ²)	Silt	4-8 lbs/ft ² (20-50 kg/m ^{2m})	Clay	2-4 lbs/ft ² (10-20 kg/m ²)
	Primary Soil Type	Typical Application Rate*							
	Sand	8-10 lbs/ft ² (40-50 kg/m ²)							
	Silt	4-8 lbs/ft ² (20-50 kg/m ^{2m})							
Clay	2-4 lbs/ft ² (10-20 kg/m ²)								
*Application rates are for a soil/bentonite liner mixed in a layer 6 inches (150mm) in thickness with a permeability of 1 x 10 ⁻⁷ cm/sec. Application rates above are shown for informational purposes only. All soils should be tested to determine specific application rates.									

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

© 2014 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

UPDATED: MARCH 2014

TDS_VOLCLAYCG50_AM_EN_201402_v1

