

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Wood Design

TECHNICAL CHARACTERISTICS

Available Formats:	19x19, 6x38, 16x18.5 Hexagon		
Style Description:		Glaze Application Method:	H.D.I.T. Rectified Products
Visual Characteristics:	Multi Wood Plank	Number of Faces/Screens:	4
Thickness in mm:	10 mm	Number of Punches/Molds:	4
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Rectified	Recommended Grout Joint:	2 to 4 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	4	Dynamic COF:	>0.42
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	5		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	14.75	Pieces per Carton:	6
SqFt per Pallet:	354.00	Pounds per Carton:	60.475
Boxes per Pallet:	24	SqFt per Container:	10266.00
Pallets per Container:	29		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".