



ROTAVATOR
HR 10 Hydraulic

Rotavator
HR 10 Hydraulic



Rotavator® HR 10 - 140 HY

The hydraulic driven Rotavator® for skidsteer loaders used in horticulture and landscaping.



HR 10 - 140 HY working

This Rotavator has been specially developed to be used on skidsteer loaders. The extensive HOWARD experience on development and production of rotary tillers is also shown in this product. The solid frame has been constructed for central and offset mounting and fits the quick mounting systems of most compact loaders.



Rotor

The new rotor construction is designed so that the blade pivots. This special feature enables the rotor to work in forward or reverse turning directions at an optional cutting angle. The powerful hydraulic motor with heavy duty bearings ensures that power is transferred to the blades with optimal efficiency.



Sideview

A strong guard protects the hydraulic piping and motor. The desired working depth is controlled by adjustable side shields.

Technical Specifications

Model	HR 10-140/120HY	HR 10-140/400HY
Working Width	55 in / 1.40m	55 in / 1.40m
Total Width	65 in / 1.60m	65 in / 1.60m
Length	30 in / 0.80m	30 in / 0.80m
Weight	650 lbs / 295 kg	653 lbs / 297 kg
Volume Flow	approx. 11gal/min	approx. 22gal/min
Rotor Speed	approx. 250/min	approx. 250/min
Working Depth	max 6 in / 0.15m	max 6 in / 0.15m
Max Pressure	14 psi / 200 bar	14 psi / 200 bar
Number of Blades	24	24



In Canada contact: Kongsilde Limited

231 Thames Rd. E., Exeter, Ontario, Canada N0M 1S3
Tel.: 519 235-0840 / Fax: 519 235-2931
E-mail: mail@kc.kongskilde.com

In the USA contact: Howard USA Inc.

10 S. Jefferson Street, Harvard, Illinois 60033, USA
Tel.: + 1 815 943 5401, Fax: + 1 815 943 3636
E-mail: howardusa@owc.net
Visit website: www.kongskilde.com

Dealer:



**HOWARD ROTAVATOR
GUY MACHINERY
14213 WASHINGTON ST.
IL. HWY 120 WEST
WOODSTOCK, IL 60098
(815) 338-0600**