

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Idea

## TECHNICAL CHARACTERISTICS

Available Formats:	20x20, 3x20 Bullnose		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	8
Thickness in mm:	8.7 mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Satin
Rectified:	Rectified	Recommended Grout Joint:	2 mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	<0.40
Scratch Hardness (MOHS)		Breaking Strength:	>1500 lbs
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	≥GB / ≥GLB		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16.37	Pieces per Carton:	6
SqFt per Pallet:	916.72	Pounds per Carton:	62.70
Boxes per Pallet:	56	SqFt per Container:	14667.52
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".