

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

NAME	SERIES	ICON
------	--------	------

TECHNICAL CHARACTERISTICS			
Available Formats:	24x24 Matte & Polished, 12x12 Matte, 2x2 on a 12x12 sheet & 3x24 Polished Bullnose		
Style Description:	Solid Colors	Glaze Application Method:	
Visual Characteristics:	Solid Colors	Number of Faces/Screens:	
Thickness in mm:	10.5	Number of Punches/Molds:	4
Modular Suitability:	Yes	Body Type:	PORCELAIN (>.5%)
Application:	Residential / Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	0	Surface Type:	Matte / Polished
Rectified:		Recommended Grout Joint:	

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	<0.5%	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	0.58
Scratch Hardness (MOHS)	7	Breaking Strength:	
Frost Resistant:	YES	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - 24x24 <i>Please inquire with Customer Service for additional sizes</i>			
SqM per Carton:	11.62	Pieces per Carton:	3
SqM per Pallet:	371.84	Pounds per Carton:	4.46
Boxes per Pallet:	32.00	SqM per Container:	
Pallets per Container:	30.00		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".