

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**NOE**

## TECHNICAL CHARACTERISTICS

Available Formats:	9X48		
Style Description:	Wood Plank	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	25
Thickness in mm:	9.5mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	1,5mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	35-45N/mm <sup>2</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	RESISTS
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	14.85	Pieces per Carton:	5
SqFt per Pallet:	668.25	Pounds per Carton:	
Boxes per Pallet:	45	SqFt per Container:	
Pallets per Container:	19		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".