



# Spectrol<sup>TM</sup>

## Product

(031918 Edition)

## Spectrol Gear Oil GL-1 85W-90

### Features

**Spectrol Gear Oil GL-1 85W-90** gear lubricant is designed for use in automotive and heavy-duty equipment transmission and differentials where an EP (extreme pressure) lubricant is not required and where API Service Designation GL-1 gear oil is specifically called for by the equipment manufacturer.

### Applications

- Heavy-duty manually operated transmission and gear boxes requiring API-GL1 lubricants
- Spiral bevel and worm axles
- Steering gears, universal joints, and spline shafts
- Enclosed industrial gears and flexible couplings

Note: not recommended for hypoid gears

### Benefits

- Good oxidation stability helps provide long service life
- Low foaming tendency
- Compatible with other gear oils

### Typical Physical and Chemical Properties

Viscosity Grade.....	85W-90
Kinematic Viscosity @100°C, cSt.....	15.5
Kinematic Viscosity @40°C, cSt.....	157.0
Viscosity Index.....	100
Flash Point, °C (°F).....	230(446)
Pour Point, °C.....	-12
Density, S.G.....	0.888
Brookfield @(-12°C)(cP).....	<150,000

Typical values are listed. Variations not affecting the performance of this fluid may occur during production however; these variations will not fall outside of set specification parameters.