

5.000" OD, HWDP, WELDED, STANDARD, 6.625" OD x 3.000" ID, DPM-DS50

HEAVY WEIGHT DRILL PIPE BODY

Nominal OD (in)	5.000
Nominal ID (in)	3.000
Pipe Grade	AISI 1340
Heavy Weight Type	STANDARD
HWConstruction	WELDED
Pipe Wall Thickness (in)	1.000
Cross Sectional Area of Pipe Body (in ²)	12.566
Cross Sectional Area OD (in ²)	19.635
Cross Sectional Area ID (in ²)	7.069
Section Modulus (in ³)	10.681
Polar Section Modulus (in ³)	21.363
Torsional Strength (lbs/ft)	56,496
Tensile Strength (lbs)	691,150
Burst Pressure (psi)	22,647
Collapse Pressure (psi)	17,600

HEAVY WEIGHT DRILL PIPE CONNECTION

OD (in)	6.625
ID (in)	3.000
Connection	DPM-DS50
Torsional Strength (lbs/ft)	83,061
Tensile Yield Strength (lbs)	1,397,293
Tool Joint/Drill Pipe Torsional Ratio (New)	1.47

HEAVY WEIGHT DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.81
Closed End Displacement (gal/ft)	1.18
Fluid Capacity (gal/ft)	0.37
Drift Size (in)	2.750
Adjusted Weight (lbs/ft)	52.97
Hardbanding	ARNCO 100 XT

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.