

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

CRAYONS

## TECHNICAL CHARACTERISTICS

|   |                        |                           |                       |
|---|------------------------|---------------------------|-----------------------|
| Available Formats:                        | 3x12                   |                           |                       |
| Style Description:                        | Pure White Body        | Glaze Application Method: | H.D.I.T Inkjet        |
| Visual Characteristics:                   | Fume or "Subway"       | Number of Faces/Screens:  |                       |
| Thickness in mm:                          | 10 MM                  | Number of Punches/Molds:  |                       |
| Modular Suitability:                      |                        | Body Type:                | Ceramic               |
| Application:                              | Residential/Commercial | Color Body Unglazed:      | Glaze Pure White Body |
| Recycled Content:<br>Post or Pre Customer |                        | Surface Type:             |                       |
| Rectified:                                | No, Pressed            | Recommended Grout Joint:  | 2MM                   |

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |                 |   |                      |
|------------------------------|-----------------|---|----------------------|
| Water Absorption:            | Between 10%-20% | Static COF:                                 |                      |
| Shade Variation (1, 2, 3, 4) | V2              | Dynamic COF:                                | N/A                  |
| Scratch Hardness (MOHS)      |                 | Breaking Strength:                          | 17 N/mm <sup>2</sup> |
| Frost Resistant:             | No              | Thermal Shock Resistance:                   |                      |
| PEI/Abrasion Resistance:     | N/A             | Deep Abrasion Test<br><175mm <sup>2</sup> : |                      |
| Chemical Resistance:         | Class A         |   |                      |

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

|                        |        |                     |    |
|------------------------|--------|---------------------|----|
| SqFt per Carton:       | 4.25   | Pieces per Carton:  | 20 |
| SqFt per Pallet:       | 306.00 | Pounds per Carton:  |    |
| Boxes per Pallet:      | 72.00  | SqFt per Container: |    |
| Pallets per Container: | 28.00  |                     |    |

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".