

A Dorsey's More Durable



BODY STRUCTURE

- Capacity: 80,000 lbs GVWR (60,000 in 10')
- ▶ Weight: 10,300 lbs +/- 3%
- Length: 48' or 53'Width: 102" overall
- ► Coupler Height: 48"
- ▶ King Pin: Setting 30"
- ► Plate: 1/4"
- ▶ Main Beams: Fabricated high tensile steel
- ► Flanges: Grade 130 high tensile steel, 3/8" x 5" upper and lower
- ▶ **Web:** Grade 80 high tensile steel, one piece
- ► Front Skirt: Formed steel with tapered corners
- ► Rear Skirt: Extruded aluminum with integral stake pockets
- Bumper: US DOT and transport canada compliant rear impact bumper
- ► Cross Members: 4" steel I-beam on 12" centers
- Cross Member Knee Brace: Fabricated one piece steel on 60" centers
- ► **Side Rail:** Extruded aluminum with integrated "LL" and J-hook track
- ► Rub Rail: 3/8" x 3" Aluminum (recessed for DOT tape)
- ► Stake Pockets: Aluminum, external mount, 24" on center with double pipe spools
- ► Floor: Extruded aluminum with 4 nailers
- ► Load Securement: Extruded double "L" (road side) with 12 winches and J-hook track (both sides)
- Mud Flaps: Heavy duty, white, anti-spray, anti-sail
- Paint: White Blasted, Two Part Primer, Two Part PPG Black Acrylic Urethane
- Lighting: Grote LED sealed lights, Grote sealed wiring harness
- ► Other: Conspicuity treatment complies with all regulatory requirements

COMPONENTS

- ► Kin Pin: 2" Holland AAR
- Landing Gear: Jost-heavy duty
 2-speed gear drive, 140,000 lb static
 load capacity
- Suspension: Heavy duty air ride, 23,000 lb. capacity
- Axles: Heavy duty, 22,500 lb. capacity
- ABS Brakes: Bendix, 2S1M
- ▶ Brakes: 16 1/2" x 7" quick change
- Hubs: Standard cast, hub-piloted, 10-stud unimount, oil lubricated
- Brake Drums: Standard cast, outboard mount
- ► Wheels: Hub piloted steel
- ► Tires: Double coin radials

OPTIONS

- Custom lengths upper and lower decks
- Custom widths
- Multiple axle configurations
- Heavy duty beam packages
- Lift axles
- Toolbox(es): Steel or Aluminum
- Heavy duty coil package
- D rings
- Strobe lights
- Wide load lights
- Custom light package
- Hub-odometer
- Tire inflation system
- ► Bulkhead: Steel or Aluminum
- ► Aluminum floor sills



334-897-2525 · www.dorseytrailer.net

Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment.