

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

NAME	SERIES	AMERICAN SLATE
------	--------	-----------------------

TECHNICAL CHARACTERISTICS			
Available Formats:	20x20, 12x24, 13x13, 2x2 Mosaic 13x13 Sheet, Cut-to-Size 6x6 & 3x13 Bullnose		
Style Description:	Slate	Glaze Application Method:	Rotocolor
Visual Characteristics:	Structured-cleft Surface	Number of Faces/Screens:	N/A
Thickness in mm:	.445-.46	Number of Punches/Molds:	N/A
Modular Suitability:	Yes (Dry-lay First)	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16th

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	< .5%	Static COF:	Wet: 0.60 Dry: 0.60
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	.48
Scratch Hardness (MOHS)	9	Breaking Strength:	>3908 lbs per SqIn
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	Yes		

PACKING INFORMATION - 20x20 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	16.27	Pieces per Carton:	6
SqFt per Pallet:	780.96	Pounds per Carton:	70
Boxes per Pallet:	48	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".