

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

PALMETTO

TECHNICAL CHARACTERISTICS

Available Formats:	23x23		
Style Description:	Travertine	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	6
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.53
Scratch Hardness (MOHS)	5	Breaking Strength:	2914 N
Frost Resistant:	Yes	Thermal Shock Resistance:	<0,06 MM/M
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	GLB		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.08	Pieces per Carton:	5
SqFt per Pallet:	578.60	Pounds per Carton:	67.98
Boxes per Pallet:	32	SqFt per Container:	15622.20
Pallets per Container:	27		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".