Woodwind Lakes Application

Fence

In accordance with the governing documents of your Association, all exterior improvements and/or changes from the original construction must be submitted for and approved by the Architectural Control Committee. Failure to receive approval may result in fines, removal, and alteration of the improvement. You should be notified within 15 days. If not, contact Sterling ASI.

Please complete the application below in its entirety and return to:

Sterling Association Services, Inc. Phone: 832.678.4500 P O Box 38113 Fax: 832.604.7093

Houston TX 77238-8113 Email: servicedesk@sterlingasi.com

Attn: WWL Improvement Application

Property Address:

Name:	
Phone Number(s):	
Email:	
Mailing Address (if different):	
No application will be considered information. A copy of property su	and will be denied automatically without completing the following urvey must also be attached which indicates location of replacement be filled out and saved by using Adobe Acrobat. d out.
A new wooden fence will be to replace	ce the existing fence along the same fence line.
A portion of the new wooden fence w	vill be on a new fence line. Indicate on the property survey the location of proposed fence
Wooden fence segments not eligible f for a total of 6 feet 6 inches.	for 8-foot height* will conform to the height requirements (6-foot picket, 6-inch rot board
The new wooden fence will be stained.	Yes No
	Behr #DP533 Cedar Natural Tone Behr Wood Finish #501 Cedar Natural Tone Olympic #716 Cedar Natural Tone
A portion of the new fence requires a	in 8-foot height* and will conform to the height requirements in the specifications.
New fence will be a black wrought iro	on fence along the perimeter of the lake and along the existing fence line.
New fence will be a breezeway gate/fo	ence. Please describe:
	Date:

A few important things to note:

Pickets MUST be No. 2 or better Western Red Cedar. Posts, stringers, and rot board may be pressure treated pine.

*Fence segments that make the perimeter of Section 4 along Philippine, Gessner, Mauna Loa and Windfern must be replaced with an 8' fence segment made up of a 12" rot board and 7' pickets.