

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**B&W**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Solid	Glaze Application Method:	
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	10.5	Number of Punches/Molds:	4
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	No	Surface Type:	Matte & Natural
Rectified:	Rectified	Recommended Grout Joint:	2mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.58
Scratch Hardness (MOHS)	7	Breaking Strength:	S>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.62	Pieces per Carton:	3
SqFt per Pallet:	371.84	Pounds per Carton:	52.871
Boxes per Pallet:	32	SqFt per Container:	11155.20
Pallets per Container:	30		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".