



cool your life...

Product Symbols

Film Type

- G - Glue Tinted Film
- C - Ceramic Film
- S - Scratch Resistant Coating
- 2 - 2 ply
- R - Reflective Film
- MG2S - Metallized Glue Tinted film, 2 ply + Scratch Resistant Coating
- MS - Metallized Film + Scratch Resistant Coating
- M2S - Metallized Film, 2ply + Scratch Resistant Coating
- HMS - Heavy Metallized Film + Scratch Resistant Coating
- HM2S - Heavy Metallized Film, 2ply + Scratch Resistant Coating
- S2S - Sputter film + 2 ply + Scratch Resistant Coating
- SN2S - Sputter Nano Hybrid Film + 2 ply + Scratch Resistant Coating
- NS - Nano film + Scratch Resistant Coating
- SAFE - Safety Film and Scratch Resistant
- T - Two Tone Gradual Film
- DEC - Decorative Film
- L - Laser Film



Product code

Film Type – Color – Visible Light Transmittance

Example : G2S-BLACK-10

G2S series (Glue Tinted Film, 2ply with Scratch Resistant Coating)

Color in BLACK

Visible Light Transmittance 10%

Product Specifications

Sputter Film (S2S Series)

For automobile, residential or commercial application.

Scratch resistant / 2 layer / 1.5mil

Warranty 7 years.

Product Code	Infrared Rejection	Shading Coefficient	Solar Energy Absorbance	Solar Energy Reflectance	Solar Energy Transmittance	Total Solar Energy Rejected	UV Reduction	Visible Light Reflectance – Exterior Reflectance	Visible Light Reflectance – Interior Reflectance	Visible Light Transmittance
S2S-A20	84%	0.35	38%	45%	17%	70%	99%↑	49.4%	45.2%	20%
S2S-A25	72%	0.40	46%	34%	20%	60%	99%↑	35.6%	33.2%	25%
S2S-A40	58%	0.50	47%	23%	30%	40%	99%↑	23.2%	19.8%	39%
S2S-A50	48%	0.60	41%	17%	42%	35%	99%↑	17.8%	13.6%	50%
S2S-N07	93%	0.48	63%	20%	17%	75%	99%↑	45.8%	25.4%	7%
S2S-N15	87%	0.50	43%	42%	15%	70%	99%↑	47.8%	40.3%	13%
S2S-N25	79%	0.52	51%	30%	19%	65%	99%↑	35.8%	27.4%	24%
S2S-N40	66%	0.55	44%	18%	38%	50%	99%↑	23.2%	16%	41%
S2S-N50	61%	0.60	47%	16%	37%	45%	99%↑	17.8%	13.6%	45%

Sputter Nano Hybrid Film (SN2S Series)

For automobile, residential or commercial application.

Scratch resistant / 2 layer / 1.5mil

Warranty 7 years.

Product Code	Infrared Rejection	Shading Coefficient	Solar Energy Absorbance	Solar Energy Reflectance	Solar Energy Transmittance	Total Solar Energy Rejected	UV Reduction	Visible Light Reflectance – Exterior Reflectance	Visible Light Reflectance – Interior Reflectance	Visible Light Transmittance
SN2S-A08	86%	0.50	53%	30%	17%	70%	99%↑	45%	20.6%	8%
SN2S-A15	77%	0.52	43%	20%	27%	65%	99%↑	29.4%	15.2%	15%
SN2S-A25	63%	0.52	50%	15%	35%	50%	99%↑	17%	11.2%	26%
SN2S-B07	87%	0.50	53%	30%	17%	75%	99%↑	45%	19.6%	7%
SN2S-B15	78%	0.52	43%	20%	27%	65%	99%↑	28.6%	14.4%	14%
SN2S-B22	66%	0.55	51%	14%	35%	50%	99%↑	15.8%	10.2%	22%
SN2S-C10	85%	0.35	38%	45%	17%	70%	99%↑	50%	21%	9%
SN2S-C15	75%	0.52	43%	20%	27%	60%	99%↑	29.6%	13%	14%
SN2S-C25	58%	0.58	52%	13%	35%	45%	99%↑	18%	10.8%	26%

Nano Film (NS / N2S Series)

For automobile, residential or commercial application.

No metals.

Scratch resistant / 1.5mil

Warranty 7 years.

Product Code	Infrared Rejection	Layer	Reflective	Thickness	Total Solar Energy Rejected	UV Reduction	Visible Light Transmittance
N2S-N35	57%	2	No	1.5mil	50%	99%↑	35%
NS-P75	75%	1	No	1.5mil	60%	99%↑	75%