

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

NAME	SERIES	NEWPORT
------	--------	---------

TECHNICAL CHARACTERISTICS			
Available Formats:	9X30		
Style Description:	Rustic Wood Blend	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Weathered Wood Look	Number of Faces/Screens:	
Thickness in mm:		Number of Punches/Molds:	16
Modular Suitability:	Yes	Body Type:	Gres Porcelain
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Flat/ Matte
Rectified:		Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:		Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	≥0.29
Scratch Hardness (MOHS)	Yes	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

PACKING INFORMATION - 9x30 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	15.08 sq ft	Pieces per Carton:	8
SqFt per Pallet:	723.84 sq ft	Pounds per Carton:	59.41 lbs
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:			

**Note:**

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".