

1.0 MP/720P IP Camera Dome with WiFi



1. Product Feature

- ✧ 1/4" line scanning digital and advanced DSP technology
- ✧ Picture Resolution 720P color CMOS , 1.0 Mega Pixel, 1280X720
- ✧ Optimized H.264 Main Profile compression algorithm, high compression ratio and high quality image; convenient to realize a transmission of HD images on a narrow band, thus it can save the storage space; support triple bit streams
- ✧ The most advanced network delivery server technology ,Easily achieve more user access , Multi-stage user password rights management
- ✧ Built in Web Server, through the IE browser easy to realize the remote control Settings prison see operation
- ✧ Support facilities remote security upgrade function
- ✧ Support DDNS 、 PPPoE and (UPnP) , Support Lan 、 Wan transport.
- ✧ Technology of self adaptability to network that it may adjust its video frame rate automatically according to the bandwidth of network
- ✧ Functions of alarm in video missing, mobile detection or probe, etc. (available to set the regions and sensitivity)

- ◇ Support mobile detection / image shielding / image snapshot
- ◇ Functions of auto recovery in abnormality and auto reconnection in network breakdown



2. Product Specification

	Model	IPC3F2BP-I2-W
Camera	Pixel	1.0 Mega Pixel, 1280*720
	Lens	3.6mm (6mm optional)
	Electronic shutter	1/25s-1/30,000s
	Low Lux	Color: 0.6Lux@F1.2 B/W: 0.08Lux@F1.2
	ICR	Support
	Video parameter	Saturation, brightness, contrast ratio and color tone can be adjusted by customer end or IE explorer
IR	IR Properties	Dual filter day / night: automatic switch, linkage switch
	IR Light	15pcs 5Φ IR LEDS, IR Distance: 15-20M
Audio-video coding parameters	Compression	H.264 Main Profile @Level 3.0 / MJPEG optional
	Video bit rate	0.1M-6Mbps, customized
	Bit stream type	video stream
	Triple bit streams	Support
Image	Video resolution	1280*720
	Video frame rate	PAL: 1-25 frames/second, NTSC: 1-30 frames/second
	Heartbeat mechanism	Support
	IP auto pop-out	IP auto pop-out at customer end
	Password protection	Multi-level protection on password
	Intellectual alarm	Mobile detection, video shielding, video loss, network breakdown, abnormality in storage
	Basic functions	One-key reset, password protection, watermark technology
Interface	DC 12V Power input	YES
	Network port	1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port
Wireless network	WIFI	YES
	Cell phone monitor	Support
	Power supply	DC12V/1.5A
	Power consumption	<6W
	Working temp	-10℃ ~ +55 ℃
	Working humidity	10 ~ 85%
	Dimension	(D)105* (H)80.8mm
	Weight	0.5Kg