



www.porterpreston.com

Tel: (866) 753-1113 • Fax: (203) 597-8828 email us at customerservice@porterpreston.com

# Woodlore® Plus Shutters

Program Reference Guide 2019

### 2019 Log

Effective Date	Topic	Section	Note	
2019/01/01	Colors Option Louvers Options Frame Options	All except j&o	2019 updated specification	
Middle of January 2019	Motorized	o	2019 updated specification	
2019/01/10	Track	<mark>j 2</mark>	Add 3" louver for Open bypass	
2019/02/01	color	e,I,n	Add 6 new hinge colors Change color coordination chart	

<b>Fable</b>	of Contents	Page
a.	Features & Benefits	WLP a-1
b.	Colors & Louvers	WLP b-1
с.	Stiles	WLP c-1
d.	Panel Configurations	WLP d-1
e.	Frame Styles	WLP e-1
f.	General Product Specifications	WLP f-1
g.	Tilt Rods	WLP g-1
h.	Divider Rails	WLP h-1
i.	Hardware	WLP i-1
j.	Track Shutters	WLP j-1
k.	Special Options	WLP k-1
1.	Hardwood Specialty Shapes	WLP l-1
m.	<b>Pricing</b>	WLP m-1
n.	Appendix	WLP n-1
Ο.	RF Motorized Shutter	WLP o-1

### Features and Benefits

- Built around the concept of modern convenience, Woodlore<sup>®</sup> plus combines wood composite frames with durable ABS louvers. Wood composite materials used are harvested from well-managed forests and finished with a polypropylene coating that prevents moisture absorption and allows for easy stain removal. ABS co-polymer louvers are dimensionally stable, which resist cupping, warping and twisting.
- 36" wide single panel for enhanced view.
- Reinforced engineered stiles Stile core durability reinforced with multiple layers of wood bonded together. The result is a robust support system for shutter panels.
- **UV inhibitor** protects shutters and home décor from UV rays, prevents color fading and sun damage.
- Multiple stile options are available in various sizes to accommodate different window configurations. Astragal or Rabbet stiles provide a natural light block between panels.
- A wide range of **frames with inserts**, which keep installation screws out of sight for a clean and decorative look, match any style and preference.
- Personalize shutters with special options. Choose from fixed louvers, hidden or offset tilt rods, café styles, bay and corner window shutters, track systems and many more.
- Quick and easy on-site assembly and installation with the pre-installed magnets and hinges, pre-mitered frames and slotted keyholes.


#### For Waterproof Option:

- The special option is perfect for wet or moisture prone areas in the home.
- Featuring enhanced resistance to moisture, shrinking and warping, the shutter frame, stile and louvers are made from durable and waterproof ABS co-polymer
- The unique UV inhibiting finish is designed for a virtually worry-free solution.
- Stainless steel hinges included in the option are guaranteed never to rust or corrode.


### Colors & Louvers

No.	Color ID	Color Name
1	<mark>001</mark>	Pure White
<mark>2</mark>	002	Extra White
<mark>3</mark>	003	Silk White
4	004	Bright White
<mark>5</mark>	006	Pearl Pearl
<mark>6</mark>	007	Ivory Lace
<mark>7</mark>	009	Creamy
8	<mark>012</mark>	Crisp Linen
9	<mark>016</mark>	Butter
<mark>10</mark>	<mark>019</mark>	String
<mark>11</mark>	<mark>030</mark>	Moondust
<mark>12</mark>	032	Sea Mist
<mark>13</mark>	<mark>042</mark>	Hall Gray
<mark>14</mark>	<mark>046</mark>	Ice
<mark>15</mark>	<mark>048</mark>	Chai
<mark>16</mark>	<mark>049</mark>	Stone Gray
<mark>17</mark>	<mark>051</mark>	Brown Gray
<mark>18</mark>	<mark>053</mark>	Clay
<mark>19</mark>	<mark>063</mark>	Decorators White
<mark>20</mark>	<mark>066</mark>	Winchester White 2010
<mark>21</mark>	<mark>073</mark>	Sky Gray
<mark>22</mark>	<mark>074</mark>	Element Gray
<mark>23</mark>	<mark>075</mark>	Storm Gray
<mark>24</mark>	<mark>077</mark>	Dawn
<mark>25</mark>	<mark>078</mark>	Cloud Blue
<mark>26</mark>	<mark>080</mark>	Taupe Gray
<mark>27</mark>	<mark>836</mark>	Classic Black

Louvers					
Elliptical	1 ½" 2 ½" 3" 3 ½" 4 ½"				



# Stiles Options



Note: 1 5/8" and 2 1/4" stile is not available for Waterproof option.

### Stiles (continued)

### Stile between panel closure

#### Single panel

- I) Panel width < 9"
  - Rabbeted stile (Deco frame, L frame, Z frame and Hang strip beside panel)
    - ° 1 <sup>5</sup>/<sub>8</sub>"
    - ° 2" (default)
  - Butt stile only (Hang strip behind panel)
    - $\circ$  1  $\frac{5}{8}$ " (Optional for panel width  $\leq$  12")
    - ° 2" (default)
- II) Panel width > 9"

Butt stile only

- $\circ$  1  $\frac{5}{8}$ " (Optional for panel width ≤ 12")
- ° 2" (default)


#### 2 panels or more

- Rabbet stile
  - $\circ$  1 <sup>5</sup>/<sub>8</sub>" (Optional for panel width ≤ 12")
  - o 2" (default)
- Astragal stile
  - ∘ 1 <sup>5</sup>/<sub>8</sub>"
  - o 2"






# **Panel Configurations**




#### **Three Panels**




# Panel Configurations (continued)


#### **Four Panels**




#### Six Panels



# Panel Configurations - Astragal Stile




### Frame Styles



Note: Standard 1" extension for L frame for Waterproof option.

<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.



There are 2 options for the Deco frame installation when Window Size is given (Take Camber Deco frame as an example)

1. Default: light block part install into the window opening;

The window size is the exact size of the window opening;

The MFF size is the measurement of the entire shutter, including the frames;


The MFF size =Window Size + Face Width





<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.


#### 2. Optional: light block part flush with window opening.

The window size is the exact size of the window opening;
The MFF size is the measurement of the entire shutter, including the frames;
The MFF size = Window Size + Frame Back Width












<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.




<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.



Note: The 1"x3/4" Post (No Light Block) is only available for Direct Mount. And no hardware will be supplied to install it on the existing window opening.




<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.




Note: For Mission Sill Cap, the extended size at each side needs to be 1" at least.


<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.



\*Notch out corner post required if ordering Z Frame with solid drywall corner.



<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.




#### Also available

- Custom width up to 7½ "for T Posts (Made of Wood), and not available for Waterproof option
- Custom angle bay posts<sup>\*</sup> (Made of Wood for non-Waterproof and Made of ABS for Waterproof option).


#### For bay window at 170 degree or above

- > 1" T Post with 3/8" light block will be used as Bay post;
- For Hang Strip (Behind Panel) and Waterproof option, bay post will be used.




<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.

#### Pre-drill L Frames (Inside Mount Only) or Z frames:




### Extension for Deco Frame\* (Default to have full extension):



Note: When the extension thickness of the frame & T post is more than 2", the extension will not be attached with the frame and T post.



Specify dimensions in special instruction box.



<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.

### General Product Specifications

Dogarintian	Minimum	<u>Maximum</u>		
<u>Description</u>	<u>Minimum</u>	Non-Waterproof Option	Waterproof Option	
Single Panel Width (Regular)	6"	24" for 1 1/8" louver 36" for 21/2 ", 3", 31/2", 41/2" louver	24" for 1 1/4" louver 31" for 21/2 ", 3" louver 36" for 31/2", 41/2 " louver	
Single Panel Width (Bifold)	6"	24"	24"	
Single Panel Width (Bifold Track)	6"	24"	24" for 1 1/6" louver 26" for 21/2 ", 3", 31/2", 41/2" louver	
Single Panel Height	10"	120"		
Shutter Width (Without T Post)	N/A	4x single panel width (bifold) + frame		
Shutter Width (With T Post)	N/A	Unlimited (For orders shipped by sea, frames longer than 142" will spliced in the middle. For orders shipped by air, frames longer than 120" will be spliced in the middle.)		
Shutter Height	N/A	120" + frame		

#### Shutters without bottom supports

Woodlore Plus Shutters without bottom supports may sag and deform. Therefore, we strongly discourage the use of shutters for this application. We will continue to manufacture these shutters; however, they will not be covered under our warranty and will be subject to the guidelines listed below:

#### All Woodlore Plus panel configurations:

- You must inform Norman Window Fashions of situations where shutters will not have bottom support when placing the initial order.
- Informing Norman when placing such orders ensures that the factory will add extra hinges to support the panel. This will reduce the probability of the panels sagging and increase shutter integrity. You must release Norman Shutters from liability in these situations.
- If you fail to notify Norman that the shutter will be used without bottom support,
   this will constitute a misapplication of the shutter. Consequently, you will be responsible for the cost of any RGA that is submitted.
- If you want a bifold shutter, a track must be ordered to support the panels. Without a track, Norman will not manufacture the order even with liability waived.

#### **Tilt Rods**

#### Standard Tilt Rod

**Default Location:** In the middle of the panel on front side (default).




#### Offset Tilt Rod

**Default Location:** On the front side of the panel and at 1" from the louver ends on the hinged side. **Optional location:** per your request



#### InvisibleTilt™ \*



Louver tilting system embedded within panel stile. It is not available for  $1^{7}/8$ " louver. The tilting system is split when the number of louvers exceeds the limits as listed below:

Louver Size	Maximum Possible Louvers	Panel Height Range
2½"	24	54 3/4" – 57 1/4"
<mark>3"</mark>	<mark>19</mark>	<del>54 1/4" – 57"</del>
3½"	16	54 3/4" – 58"
4½"	12	54 3/4" – 60"

For even numbers of louvers, the number of louvers operated by the top and the bottom tilting system will be the same:

For odd numbers of louvers, the number of louvers operated by the bottom tilting system will be one more than the number of louvers operated by the top tilting system;

To ensure split tilt is included, always specify on the order.

#### **Split Tilt**

When customer requires the split tilt in custom position, the measurement will be as follows, please note that the louvers are in close position when measured.

#### Window size:

- Measure from the bottom of the window to the top of the louver Max frame-to-frame:
  - Measure from the bottom of the frame to the top of the louver.
- \* Surcharge applies. Please see Options and Surcharges page for details.

### **Divider Rails**

- A divider rail is an extra rail in the middle of the panel.
- Creates two sections in the panel so louvers can be operated independently.
- Strengthens the panel and enhances structural integrity.
- Required for panel heights over 78" for non-waterproof option.
- Required for panel heights over 72" for waterproof option.

#### **Specifications**


- Standard width: 3"
- · Default location: center of the panel unless specified otherwise

#### Measurements:

- Window size:
  - Measure from the bottom of the window to the center of the divider rail.
- Max frame-to-frame:

details.

- Measure from the bottom of the frame to the center of the divider rail.
- Position
  - Per customer's specification. However, the divider rail may be adjusted to a lower or higher position, within our allowable deviation, to ensure reinforcement and aesthetics of the shutter.
    When placing the order, please clearly specify if the divider rail position needs to line up with that of other shutter divider rails in the same room. Please also refer to the table below for the allowable deviation




#### Divider rail allowable deviations

Louver Size	Allowable + Deviation	
1 <del>7</del> 8"	3/4"	
2½"	1"	
<mark>3"</mark>	<mark>1 1/4"</mark>	
3½"	1½"	
41/2"	2"	


### Hardware

### Hinges


Self-Mortise Hinge




Bi-fold Hinge



L Hinge



Direct Mount 3" Hinge



Hinges are available in:

Pure White, Silk White, Bisque, Pearl, Bright Brass, Antique Brass, Black, Nickel plated, Brushed Nickel Plated and Stainless Steel\*, Crisp Linen, String, Sea Mist, Stone Gray, Brown Gray, Taupe Gray


While hinge colors of Crisp Linen, String, Sea Mist, Stone Gray, Brown Gray, Taupe Gray are not available for Direct mount 3" Hinges.


For Waterproof option, hinge color is only available in Stainless Steel, and Sleeve & Base Plate will be used as catches.

> Direct Mount 3" Hinge:

<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.

- 1. The hinge position of the direct mount 3" hinge will be different from that of the 2.375" ones. For shutters used both the 2.375" and the direct mount 3" hinge, the hinge position of the 2.375" ones will match that of the direct mount 3" hinge;
- 2. The hinge is only to install between the panel and the existing window. For other situation, 2.375" hinges will be used;
- 3. To avoid confliction, there will be cut-out for the light block of the hinged side. Please refer to the drawing below.





### **Invisible Hinge:**

- 1. Invisible hinge is not available for Multifold panels.
- 2. Invisible hinge is only used between the panel & frame / T post, between panel and panel will be used regular hinge.
- 3. Color Option: Only available for Pearl Chrome Plated.

Frame Options	Hinge	Notes
2" Camber Deco Frame	Y	<u>/</u>
2" Classic Deco Frame	Y	<u>/</u>
2.5" Mission Deco Frame	N	<u>/</u>
3" Ridge Deco Frame	<mark>Z</mark>	7
Vintage L Frame W / 1/4" Light Block	N	<u> </u>
Vintage L	N	<u>/</u>
Vintage L Frame w/ 1/2" Buildout	N	<u> </u>
Vintage L Frame w/ 1" Buildout	<mark>N</mark>	<u>Z</u>
Beaded L w 1/4"light block	Y	<b>Z</b>
Beaded L	Y	<u>/</u>
Beaded L Frame w/ 1/2" Buildout	Y	<u> </u>
Beaded L Frame w/ 1" Buildout	Y	<u> </u>

Tilt out Z Frame	N	l /
1.25" Beaded Z Frame	Y	/
2" Bullnose Z Frame	Y	/
1.5" Bullnose Z Frame	Y	<u> </u>
2" Bel Air Z Frame	Y	<u>/</u>
3" Crown Z Frame	N	<u> </u>
7/8" Vintage Hang Strip	N	<u>/</u>
Traditional Hang Strip	N	<u>/</u>
1" T-Post w/ 1/4" Light Block(for Deco)	Y	
1" T-Post w/3/4" Light Block(for L/Z/HS)	Y	
1" Chamfer T-Post w/ 1/4" Light Block(for Deco)	Y	only available with hinge on
1" Chamfer T-Post w/3/4" Light Block(for L/Z/HS)	Y	one side, for example, LTL is available, but RTL is not.
1" Chamfer T-Post w/ 1/4" thick 3/8" wideLight Block(for Deco)	Y	
1" Chamfer T-Post w/3/4" thick 3/8" wide Light Block(for L/Z/HS)	Y	
1 3/4" Chamfer T-Post w/1/4" Light Block(for Deco)	Y	available with hinge on BOTH
1 3/4" Chamfer T-Post w/3/4" Light Block(for L/Z/HS)	Y	side, for example, RTL.
Corner Post w/1/4" Light Block(for Deco)	Y	<u>/</u>
Corner Post w/3/4" Light Block(for L/Z/HS)	Y	V
Bay Post w/1/4" Light Block(for Deco)	Y	V
Bay Post w/3/4" Light Block(for L/Z/HS)	Y	<u>/</u>

### Invisible Hinge Qty:


Panel Height (H)	Hinge Qty
H<=48"	<mark>2</mark>
48" <h<=78"< td=""><td><mark>3</mark></td></h<=78"<>	<mark>3</mark>
78" <h<=96"< td=""><td><mark>4</mark></td></h<=96"<>	<mark>4</mark>
96" <h<=120"< td=""><td><mark>5</mark></td></h<=120"<>	<mark>5</mark>

#### **Preinstallation:**


Panels and frames will be packaged individually, and the hinge is preinstalled onto the frame/post, with the screws for the other half part on the panels in the hardware box.

Panel Lock: (not available for 1.625" Stile)

Available Material: All Color: Brush Nickel-Plated




Position: (Only available on Bottom for Track Shutters with Bottom Track; For Regular, available on Top/Bottom/both Top and Bottom)




The Panel Lock location for both track system shutters and regular shutters would be the same.

The general principle is that the Panel Lock position will avoid the stile which will install the spring-loaded guide at bottom (same stile as the Wheel carrier).



Ring pull: for easy opening and closing

(Not available for 1.625" Stile)



color

Please note the ring pull color will match with the hinge color.
When shutter order with Invisible Hinge, the ring pull color will match with the normal hinge color.
Please see the matching chart below:

Hinge Pure Silk Brushed Oil-Antique Bright Stainless **Bisque** Pearl Black Nickel Rubbed color White White Nickel **Brass Brass** Steel Ring Brushed Brushed Antique **Bright** Brushed Pull White White Bisque Pearl Black Black Nickel Nickel **Brass Brass** Nickel

Hinge color	Crisp Linen	String	Sea Mist	Stone Gray	Brown Gray	Taupe Gray
Ring Pull color	Bisque	Bisque	Brushed Nickel	Brushed Nickel	Brushed Nickel	<b>Brushed Nickel</b>

#### For non-waterproof option:

Color ID	Color Name	New Hinge color (Default)	New Ring pull color	New T post connector color	Invisible Hinge	Direct Mount 3" Hinge color (Default)
001	Pure White	Pure White	White	Pure White	Pearl Chrome	Pure White
002	Extra White	Silk White	White	Silk White	<u>Plated</u>	Silk White
<mark>003</mark>	Silk White	Silk White	White	Silk White		Silk White
<mark>004</mark>	Bright White	Silk White	White	Silk White		Silk White
<mark>006</mark>	Pearl Pearl	Pearl Pearl	<u>Pearl</u>	<mark>Pearl</mark>		<mark>Pearl</mark>
007	Ivory Lace	Bisque	Bisque	Bisque		Bisque
009	Creamy	Pearl Pearl	Pearl	Pearl		Pearl
012	Crisp Linen	Crisp Linen	Bisque	Bisque Bisque		Bisque


016	Butter	Crisp Linen	Bisque	Bisque	<b>Bisque</b>
019	String	String	Bisque	Bisque	Bisque
030	Moondust	Sea Mist	Brushed Nickel	Nickel Plated	Nickel Plated
032	Sea Mist	Sea Mist	Brushed Nickel	Nickel Plated	Nickel Plated
042	Hall Gray	Sea Mist	Brushed Nickel	Nickel Plated	Nickel Plated
046	Ice	Silk White	White	Silk White	Silk White
048	Chai	Nickel Plated	Brushed Nickel	Nickel Plated	Nickel Plated
049	Stone Gray	Stone Gray	Brushed Nickel	Nickel Plated	Nickel Plated
051	Brown Gray	Brown Gray	Brushed Nickel	Nickel Plated	Nickel Plated
053	Clay	Nickel Plated	Brushed Nickel	Nickel Plated	Nickel Plated
<mark>063</mark>	Decorators White	Silk White	White	Silk White	Silk White
066	Winchester White 2010	Pearl Pearl	Pearl Pearl	Pearl Pearl	Pearl
<mark>073</mark>	Sky Gray	Silk White	White	Silk White	Silk White
074	Element Gray	Sea Mist	Brushed Nickel	Nickel Plated	Nickel Plated
075	Storm Gray	Sea Mist	Brushed Nickel	Nickel Plated	Nickel Plated
077	Dawn	Silk White	White	Silk White	Silk White
<mark>078</mark>	Cloud Blue	Silk White	White	Silk White	Silk White
080	Taupe Gray	Taupe Gray	Brushed Nickel	Nickel Plated	Nickel Plated
<mark>836</mark>	Classic Black	Black	Black	Black	<mark>Black</mark>

#### For waterproof option:

	<u> </u>		_	
Color ID	Color Name	Hinge color (Default)	Invisible Hinge	Ring Pull color
001	Pure White	Stainless Steel	Pearl	Brushed Nickel
002	Extra White		Chrome	
003	Silk White		Plated	
004	Bright White			
<mark>006</mark>	Pearl Pearl			
<mark>007</mark>	Ivory Lace			
009	Creamy			
012	Crisp Linen			
<mark>016</mark>	Butter			
<mark>019</mark>	String			
030	Moondust			
032	Sea Mist			
042	Hall Gray			
<mark>046</mark>	<u>lce</u>			
<mark>048</mark>	<u>Chai</u>			

049	Stone Gray
<mark>051</mark>	Brown Gray
<mark>053</mark>	Clay
<mark>063</mark>	<b>Decorators White</b>
<mark>066</mark>	Winchester White 2010
<mark>073</mark>	Sky Gray
<mark>074</mark>	Element Gray
<mark>075</mark>	Storm Gray
<mark>077</mark>	<mark>Dawn</mark>
<mark>078</mark>	Cloud Blue
080	Taupe Gray
<mark>836</mark>	Classic Black

Position: For different panel configuration, please refer to the location of Panel Lock to show on which stile the pull will be fixed.




#### Position:

- A. Above Bottom Rail (Default)
- B. Above 1st Divider Rail (Default when there are Divider Rails)
- C. Custom Location

If both Panel Lock & ring pull are specified, the distance between them is 2 3/4", and the ring pull location is 6 3/4" from the bottom of panel.

When there is no mid rail, ring pull will be just on the top of Panel Lock (2 3/4" above Panel Lock) as default location; if there are mid rails, bottom of ring pull lines up with top of the 1<sup>st</sup> mid rail as default location.



#### Position:

- A. 2 3/4" Above Panel Lock (Default when both Ring Pull and Panel Lock are specified)
  B. Above 1<sup>st</sup> Divider Rail (Default when there are Divider Rails)
  C. Custom Location

#### Measurements:

- · Window size:
  - Measure from the bottom of the window to the center of the ring pull.
- Max frame-to-frame:
- Measure from the bottom of the frame to the center of the ring pull.


#### Side Magnet: Not available for Waterproof option

#### Available for Butt, rabbet and Astragal stile




Side Magnets will be applied in following situation:

Double Hung shutter but without horizontal T post:
 Side magnets will be applied to the meeting stiles of the L and R panel. (Default)




2. Café Shutter

Side magnets will be applied to the meeting stiles of the L and R panel. (Default)




3. No frame or light block or L-shape striker plate on either top or bottom, or if larger than standard top or bottom gap is requested.

Side magnets will be applied to the meeting stiles of the L and R panel. (Optional)




#### **T-Post Connector**





- Available colors: Pure White; White; Pearl; Bisque; Black; Nickel-Plated.
- Available for all types of T Posts (custom-width T posts excluded).

#### T Post Connector can be used with the following Frames.


L Frame: Deco Frame: Z Frame:







Hang Strip (Beside)




#### Note:

- 1. For Horizontal T Post, Hang Strip (Behind) and shutter with 1.5"/2" Sill, T Post connector is not available and T Post will be installed by screws instead;
- 2. If there is a panel lock which may interfere with the T-Post connector, all the T-Posts for the entire shutter will be installed with screws and the frames to be pre-drilled, even in cases where the panel lock may only interfere with one T-Post;
- 3. T post connectors can only be installed on a straight piece, and screws will be used instead for T Post installed on a curved or raked piece.
- 4. The screw color is Stainless Steel for Waterproof shutter regardless of the color of the T Post connector;
- 5. The screw color is Nickel Plated for Non-Waterproof shutter regardless of the color of the T Post connector;

### **Optional Poles:**

### 1. Terminology



### Component

NO.	Name	Note
1	Pole with Attachment	Steel tube, Pole Base and Bottom Cap included  *Surcharge applies.
2	Attachment only	<ul> <li>Compatible with extension poles found in most home improvement stores.</li> <li>Screw thread (3/4") and thread pitch (1/5")</li> <li>*Surcharge applies.</li> </ul>

### 2. Available Pole Length

Two lengths available:

• 32"

43"

### 2016 Track Shutters—Bypass

### **Guidelines and Specs:**

	<u>Minimum</u>	<u>Maximum</u>		
<u>Description</u>		<mark>17⁄8"</mark>	<mark>2½"/ 3"</mark>	31/2" / 41/2"
Single-Panel Width (Regular) for Non-Waterproof option	<mark>6"</mark>	<mark>24"</mark>	<mark>36"</mark>	<mark>36"</mark>
Single-Panel Width  (Regular)  for Waterproof option	<mark>6"</mark>	<mark>24"</mark>	<mark>31"</mark>	<mark>36"</mark>
Single-Panel Height	10"	120"	120"	120"

#### **Outside Mount**

Max frame-to-frame width: window width + 3"
Max frame-to-frame height: window height + 4½"

#### Semi-Inside Mount


Max frame-to-frame width: window width - 1/8" Max frame-to-frame height: window height + 1 3/8"

#### **Inside Mount**

Max frame-to-frame width: window width - 1/8" Max frame-to-frame height: window height - 1/8"

#### Carriers are in the Track / Hangers are in the Panel:

Adjustments to panel alignment are made by turning the Carrier Bolt with the wrench included in the Hardware Box






Push carrier into




# 2016 Track Shutters—Bypass

### **Top View**


### **Outside Mount**



### Semi-Inside Mount




#### **Inside Mount**




# 2016 Track Shutters—Bypass Top View

#### Combi - joined Panels (optional):

#### For Non-Waterproof option:




#### For Waterproof option:




For shutters with 4 or more panels, please select "side open" or "center open"

#### Side Open for Non-Waterproof option:




#### Side Open for Waterproof option:




# 2016 Track Shutters—Bypass


#### Center Open




#### 4 panels side open w/Rabbet stile




#### 4 panels center open w/Rabbet stile



#### 6 panels side open w/Rabbet stile



#### 6 panels center open w/Rabbet stile




Stile: Only 2", 2 1/4" rabbet stiles are available,


1 5/8" rabbet stile only used for combi-joined panels for non-waterproof option. Center stile is not available.

# 2016 Track Shutters—Bypass

## Size Definition For Semi-Inside/OM without side boards


#### For IM without side boards






Note: For Semi-Inside/OM bypass without side boards but with fascia return, 2016 Stopper will be supplied.


# Mounting Options (Closed Bypass) Side View









# 2016 Track Shutters—Bypass




**Mounting Options (Closed Bypass with 3 Tracks):** 




# 2016 Track Shutters—Bypass






# 2016 Track Shutters—Bypass




# Mounting Options (Opened Bypass) Only available in 2 ½", 3" and 3 ½" louver sizes


#### 2 1/2" Louver




# 2016 Track Shutters—Bypass




#### 3" / 3 1/2" Louver



# 2016 Track Shutters—Bypass









# 2016 Track Shutters—Bypass

#### **Opened Bypass**

#### **Top View**



Note: The light block for open bypass will be changed to use screws with wood plugs instead of current dowels.



Separation of track


- open and on the contract of					
Louver	U shape bottom guide		Interlocking bottom guide		
Louver	Regular Tilt Rod	Invisible tilt	Regular Tilt Rod	Invisible tilt	
2.5"	3 9/16"	2 3/4"	3 9/16"	3 9/16"	
<mark>3"</mark> / 3.5"	4 1/2"	3 5/8"	4 1/2"	4 1/2"	

Light block thickness for panel


Light block thickness for parier					
U shape bottom guide		Interlocking bottom guide			
Louve	er	Regular Tilt Rod	Invisible tilt	Regular Tilt Rod	Invisible tilt
2.5"	h1	3/4"	3/4"	3/4"	1 9/16"
2.5	h2	1 9/16"	3/4"	1 9/16"	3/4"
<mark>3"</mark> / 3.5"	h1	1 3/16"	1 3/16"	1 3/16"	1 15/16"
<del>3</del> / 3.5	h2	1 15/16"	1 3/16"	1 15/16"	1 3/16"

Nylon Guide: The nylon guide is composed by 2 parts and will supplied as a whole set by default (bottom part 16mm and top part 5mm), please remove the top part if necessary.

# 2016 Track Shutters—Bypass




#### The 2016 Stopper



For outside mount/semi-inside mount bypass without side boards but with fascia returns, the 2016 Stopper will be supplied by default. The gap between the fascia return and the panel is 5mm each side.

The 2016 stopper can also be used in the center or any position of the top track as an option. Please see drawing below to show the gap.



## 2016 Track Shutters—Bypass

Track Shutters Framing Materials (For waterproof option, only plain fascia is available)

Framing	Size				Pc(s)
L Shape Header	Header (Closed Bypass)	Header (Opened Bypass)	Supporting Strip		
(2 in 1)	3/4" x 51/2"* (Default for Outside Mount; Optional for Semi-Inside and Inside Mount)	<sup>3</sup> ⁄ <sub>4</sub> " x 6 <sup>1</sup> ⁄ <sub>4</sub> " <sup>*</sup> ( 2 <sup>1</sup> ⁄ <sub>2</sub> " Louver)	<sup>3</sup> ⁄ <sub>4</sub> " x <sup>3</sup> ⁄ <sub>4</sub> "		1 pc
Header with Supporting Strip	3/4" x 41/2"* (Default for Semi-Inside and Inside Mount; Optional for Outside Mount)	<sup>3</sup> ⁄4" x 7 <sup>13</sup> / <sub>16</sub> " <sup>*</sup> (31⁄2" Louver)			
	Custom <sup>*</sup> ≤ 8"	Custom * < 8"			
U Shape Side Frame	Side Frame (Closed Bypass)	Side Frame (Opened Bypass)	Supporting Strip	Side Fascia	
(3 in 1)	3/4" x 5 7/8" <sup>*</sup> (Default for Outside Mount; Optional for Semi-Inside and Inside Mount)	¾" x 6 ½" ( 2½" Louver)			2 pcs
Side Frame with Supporting Strip	3/4" x 4 7/8"* (Default for Semi-Inside and Inside Mount; Optional for Outside Mount)	³¼" x 8½" <sup>*</sup> (3½" Louver)	<sup>3</sup> ⁄4" X <sup>3</sup> ⁄4"	%" x 1¼ "	
& Side Fascia	Custom <sup>*</sup> ≤ 8"	Custom * < 8"			
Top Fascia (Plain/Deco)	4" (Semi-inside and Outside Mount)				1 pc
½" x 2 ½" (Inside Mount)					
Top Fascia	4" (Semi-inside and Outside Mount)				2 000
Return	N/A (Inside Mount)				2 pcs

#### **Track Shutters Framing Materials**


#### Note:


- When the header size is  $4\frac{1}{2}$ ,  $5\frac{1}{2}$ ,  $6\frac{1}{4}$  or  $7^{\frac{13}{16}}$ , the L Shape header and the U Shape Side Frame will be sent integrally. That is:
- 1. The header and the supporting strip will be sent integrally as L Shape Header;
- 2. The side frame, supporting strip and the side fascia will be sent integrally as U Shape Side Frame.
- For any custom header sizes other than 4½"\*, 5½"\*, 6½"\* or 7<sup>13</sup>/<sub>16</sub>"\*, the L Shape Header and the U Shape Side Frame will be sent separately. That is:

# 2016 Track Shutters—Bypass

- 1. The header and the supporting strip will be sent separately for L Shape Header;
- 2. The side frame, supporting strip and the side fascia will be sent separately for U Shape Side Frame.
- The way to connect the bypass header & Fascia: Use the L Bracket to connect the fascia returns, fascia and header. This applies for Inside Mount, Semi-Inside Mount & Outside Mount. Please refer to the drawings below.

#### **Outside Mount:**





# 2016 Track Shutters—Bypass


## Hardware Box

Hardware Box				
Part				
Wrench				
Nylon Guide				
3/4 " screws for Nylon Guide				
Support L Bracket (based on the length of header)				
2 ½ " screws for support L bracket				
3/4 " screws for support L bracket				

#### **Keystone for Fascia of the Track Shutter**


When fascia length exceeds the limitation and needs to split, keystone design fascia will be supplied without surcharge for track shutters.

For fascia length within the split limitation, keystone can also be supplied as an option with surcharge.



The keystone will be installed by screws. We will pre-drill the screw holes and the screws will be packed in hardware box.


# 2016 Track Shutters—Bypass



Plastic L Bracket to Connect the Header, Fascia & Fascia Returns



L Bracket will be used to connect the header, fascia and fascia returns for Bypass shutter. This applies for Inside Mount, Semi-Inside Mount & Outside Mount.



# 2016 Track Shutters—Bypass


# Bi-fold 180<sup>TM</sup>

#### **Guidelines and Specs:**

		<u>Maximum</u>		
<u>Description</u>	<u>Minimum</u>	<mark>1공"</mark>	2½"; 3"; 3½"; 4½"	
Single-Panel Width	- "	2	2.41	
(Bi-fold Track) for Non-Waterproof option	<mark>6"</mark>	<mark>24"</mark>	<mark>24"</mark>	
Single-Panel Width				
(Bi-fold Track)	<mark>6"</mark>	<mark>24"</mark>	<mark>26"</mark>	
for Waterproof option				
Single-Panel Width (LLL/RRR)	N/A	N/A	N/A	
Single-Panel Height	10"	<mark>120"</mark>	<mark>120"</mark>	


#### **Outside Mount**

Max frame-to-frame width: window width + 3 1/2"
Max frame-to-frame height: window height + 4 1/2"



• Track is pre-installed on the header; standard 1 track only.


#### Mounting Options: Outside Mount only




#### **Top View**

Note:


- ♦ The header will protrude the panel about 1/8" for each side.
- Header, light blocks, and bottom pivot bracket(s) must be installed on a flat surface.




#### With Existing Casing:




- ♦ Header Extension: Optional
- ♦ Custom extension up to 2" for Header
- ♦ When extension is needed, the header will protrude the panel 5/16" for each side and the fascia return will protrude the panel 11/16" for each side.



♦ The extension will be pre-attached.




For 180 Bi-fold, if Bottom Pivot L Bracket is required, the extension for the L shape light block will be 1 3/4" in width. Please see picture below:



Panel Configuration: Only 2", 2 1/4" rabbet and butt stiles are available for non-waterproof option.

Only 2" rabbet and butt stiles are available for waterproof option.

Center stile is not available.




#### Notes:

If there is no baseboard to the wall, 3" header can be used.

If there is baseboard to the wall, then it should be as below:

- 1. If base board thickness is less or equal to 5/8", 3 1/2" header can be used.
- 2. If base board thickness is over 5/8", it is suggest using the 3" header with build out. And the build out thickness=base board thickness-1/8".

#### Please see the drawing below:



180<sup>0</sup> Bi-fold Track Shutters Framing Materials

Туре	Header Dimension	Top Fascia Dimension	L Shape Light Block Strip Dimension
Header &	3"		1 9/16"
Top Fascia & Light Block Strip	3 1/2"	3 3/8"	2 1/16"

## 180<sup>o</sup> Bi-fold Track Shutters Hardware Box

Parts
Wrench
Hinge Pin
Support L Bracket (based on the length of header)
2 ½ " screws for support L bracket
3/4 " screws for support L bracket
Bottom Pivot Bracket
1 ½ " screws for bottom pivot bracket
2 ½ " screws for Frame with predrilled screw holes

## Bi-fold 90

**Guidelines and Specs:** 

Description	Minimum	<u>Maximum</u>		
Description	<u>wiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii</u>	11/8"	2½"; 3"; 3½"; 4½"	
Single-Panel Width (Bi-fold Track) for Non-Waterproof option	<mark>6"</mark>	24"	<mark>24"</mark>	
Single-Panel Width (Bi-fold Track) for Waterproof option	<mark>6"</mark>	<mark>24"</mark>	<mark>26"</mark>	
Single-Panel Width (Multifold track up to 4 panels)	N/A	N/A	N/A	
Single-Panel Height	10"	<mark>120"</mark>	120"	


#### **Outside Mount**

Max frame-to-frame width: window width + 3 1/2" Max frame-to-frame height: window height + 4 1/2"

Semi-Inside Mount

Max frame-to-frame width: window width - 1/8"
Max frame-to-frame height: window height + 1 3/8"
Inside Mount


Max frame-to-frame width: window width -  $^{1}/_{8}$ " Max frame-to-frame height: window height -  $^{1}/_{8}$ "



Track is pre-installed on the header; standard 1 track only.

**Mounting Options: Outside Mount** 

**Side View** 




#### Without Casing:


### **Top View**



- ♦ Fascia return will protrude the panel about 1/2" for each side.
- ♦ The header will protrude the panel about 1/8" for each side.
- Header, light blocks, and bottom pivot bracket(s) must be installed on a flat surface.




#### With Existing Casing:




#### Semi-Inside/Inside Mount


#### **Side View**




#### Semi-Inside Mount Top View



#### Inside Mount Top View




- ♦ Header Extension: Optional.
- ♦ Custom extension up to 2" for Header
- ♦ The extension will be pre-attached.




Panel Configuration: Only 2", 2 1/4" rabbet and butt stiles are available for non-waterproof option. Only 2" rabbet and butt stiles are available for waterproof option. Center stile is not available.

#### LL or RR



## 90° Floating Panels





- either direction
- Application comes with wheel carrier, spring loaded guide and floor track
- Can be used on large window

1. For 90° Floating Panels outside mount/semi-inside mount without side boards but with fascia return, the 2016 Stopper will be supplied by default. The gap between the fascia return and the panel is 5mm each side.

The 2016 stopper can also be used in the center or any position of the top track as an option.


#### 2016 Stopper






2. When rabbet stile required, the meeting stile of unhinged stile will be butt stile by default.





Note: When Butt/rabbet Stile is required, the stile next to the hang strip will be astragal stile.



# 90 degree Bi Fold Track Shutters Framing Materials (For Waterproof option, only plain fascia is available)


Туре		Header Dimension	Top Fascia Dimension	Light Block Strip Dimension	Hang Strip Dimension
Header &	ОМ	3"		1 9/16"	
Top Fascia&	Olvi	3 1/2"	3 3/8"	2 1/16"	
Light Block	Semi-IM	3"		5/8"x3/4"	
Strip	IM	3"	1 7/8"	5/8"x3/4"	1.08"x0.875"

Note: It will be L shape light block strip for outside mount.


#### Frame Hinged Bifold (Not available for Waterproof option)

**Available Stile: Rabbet Stile Only** 

**Available Frame type** 





**Vintage Hang Strip with 13mm light block:** For single direction shutter with even panel qty, the frame on the unhinged side will be Vintage Hang Strip with 13mm [0.512"] light block, the height of the Vintage Hang Strip will match with that of the hinged side frame. The Vintage Hang Strip will be made in wood with surcharge.



#### **Top View**

Hinged at Left or Right with wheel assembly at top;







#### **Side View**


**Outside Mount** 

3-Sides + bottom light block




3-Sides + 3" Deco Sill Frame






Note: For OM Frame Hinged Bifold shutter not to use as a door, if there is no existing sill at the bottom of the window opening, it is recommended to have the 3" Deco Sill Frame at the bottom.


# Semi-Inside 3.1[1/8] 3.1[1/8] Window Height




For frame hinged bifold track shutter used as door, the bottom gap will be 19mm by default. Please specify "Used As Door" on the order form.




#### Panel Configuration (uneven panel width)





#### Notes:


1. Only available for 3-Sides + bottom light block or 3-Sides + 3" Deco Sill Frame (4-sides is not available); Panels can be folded and open at 90 degree;



- 2. Frames available: Only Vintage L Frame
- 1) For top frame, the insert will be replaced by top fascia;
- 2) Top track will be pre-attached to the top frame;
- 3) Frame will be pre-drilled with screw holes same as regular shutters.

**Ring Pull:** The ring pull will be provided as option; and for frame hinged bi-fold, the ring pull will be supplied as default; Customer need specify ring pull location on the order form. Ring pull location is measured from the floor to center of the ring pull in height direction. Ring pull color will match the hinge color.

Please refer to below drawing of ring pull position for all shutter type:



#### **Bottom Pivot Bracket for 90 degree bifold:**

For 90° Bifold Track Shutter, there will be 2 types of Bottom Pivot Brackets available.




For Inside Mount, Bottom Pivot L Bracket will be supplied as default;




For Semi-Inside or Outside Mount, bottom pivot bracket will be supplied as default.

For 180° Bifold Track Shutter, 81mm Bottom Pivot L Bracket will be supplied as default.




#### **Track Dimension:**


Top Track



Extra Magnets will be supplied for Bifold hinges: (only for the most top and bottom hinges, not available for Waterproof option)



**Side Magnet:** applied to the meeting stiles of LR panels, not available for Waterproof option



Extra magnet and Side Magnet (Not available for Waterproof option)




#### 90<sup>0</sup> Bi Fold Track Shutters Hardware Box

Parts
Wrench
Hinge Pin
Support L Bracket (based on the length of header)
2 ½ " screws for support L bracket
3/4 " screws for support L bracket
Bottom Pivot Bracket
38.1mm screws for bottom pivot bracket
63.5mm screws for Frame with predrilled screw
holes

#### Notes:

- 1. for all bifold track shutter Outside Mount, the header will be pre-drilled with screw holes in the insert and screws will be supplied by default;
- 2. for all bifold track shutter Inside/Semi-Inside Mount, the header will be pre-drilled with holes for screws and wood plug and screws and wood plug will be supplied by default



3. For both 90° & 180° bi-fold track, for waterproof option, when 3" header is selected, the header will make as 2 3/8" (Vintage L frame for waterproof option) + 5/8" extension.

When 3 1/2" header is selected, the header will make as 2 3/8" (Vintage L frame for waterproof option) + 1 1/8" extension.


The extension for both header sizes will be pre-attached.

4. For waterproof option, only plain fascia is available.


#### **Keystone for Fascia of the Track Shutter**

When fascia length exceeds the limitation and needs to split, keystone design fascia will be supplied without surcharge for track shutters.

For fascia length within the split limitation, keystone can also be supplied as an option with surcharge.




The keystone will be installed by screws. We will pre-drill the screw holes and the screws will be packed in hardware box.



# **Special Options**

#### Café Shutters


- The top of the panel requires a special finish. Please indicate "café shutter" when placing orders.
- The shutter does not come with recessed magnet on top.






#### **Double-Hung Shutters**\*


- For total number of panels, please include panels in both rows.
- Bifold panel is not available under this option.
- For panel configuration, please provide panel fold for one row.
- The default location for the division point is the center unless specified otherwise.
- Horizontal T Post<sup>\*</sup> can be added for increased structural integrity.
- Warranty needs to be waived for the horizontal T post length exceeds 48".








#### **Fixed Louvers**











#### Batten for Type E&F: (Not available for Waterproof option)

The batten is placed behind the Type E/F panel to block light.

Louver size	Batten Width	Batten thickness
1 7/8" & 2 1/2"	3/4"	1"
3" / 3 1/2"	3/4"	1 3/8"
4 1/2"	3/4"	1 7/8"

WLP k-1

Surcharge applies. Please see Options and Surcharges page for details.

# Special Options (continued)

#### Custom Colors

Available in Woodlore® plus shutters.

Option (Color Code)	Sample Size	Confirmation Process
Custom Solid (C01)	At least 4" x 4" on a clean, flat surface such as wood or cardboard	All orders require customer's confirmation via actual swatch in the mail before production. Additional shipping and handling fee applies.

#### Note:

- 1) All custom colors will only be finished with the standard gloss used on all Norman products.
- 2) Please note that we will only be able to match the tone instead of the texture or finish of the sample your submit.
- 3) Only one dispute is allowed during the color confirmation process.
- 4) Customer may waive confirmation to shorten production lead time. Norman<sup>®</sup> will not be responsible for any color variation afterwards.

#### Disclaimer:

Benjamin Moore, Benjamin Moore Classic Colors, Sherwin Williams ColorSnap and Sherwin Williams Designer Expressions are registered trademarks or trademarks of their respective owners. All other trademarks mentioned herein are the property of Norman International, Inc. and/or its affiliates in the U.S. and certain other countries. Reference herein to the commercial products or service of others by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement.


<sup>\*</sup>Surcharge applies. Please see Options and Surcharges page for details.


## Hardwood Specialty Shape

### Specialty Shutters (Not available for Waterproof option)

Specialty shutters are made of premium solid wood, finished to match the beauty of all Norman shutters. Templates are required if it is an imperfect specialty. Delivery time is 8 weeks from the order confirmation date for all specialty shutters. Please refer to Specialties and Template Requirement sections for details.

All frames for specialty shutters will be made as solid frames (not with an insert). However, if there is a regular shutter below a specialty shutter and the frames for both shutters are separated by a divider strip, then the top frame will be made as a solid frame but the bottom frames will be made as regular frames with inserts. If the top frames and the side frames are not separated by a divider strip, both side frames and the bottom frames will be made as solid frames.





# Pricing

1) By Max Frame-to-Frame M	easurement:						
Regular Shutter	cusurement.						
Inside and Outside Mount	Width	х	Height	/ 144	Х	\$/sq ft	
Track Shutter**							
Inside	Width	х	Height	/ 144	х	\$/sq ft	
Semi-Inside and Outside Moun	Width	х	(Height-11/2")	/ 144	Х	\$/sq ft	
2) By Net Panel Measuremen	Width	х	Height	/ 144	х	\$/sq ft	
3) By Window Size:							
	4-sided	(Width+4")	Х	(Height+4")	/ 144	х	\$/sq ft
2" Camber Deco Frame	3-sided with Sill Plate	(Width+4")	х	(Height+4")	/ 144	х	\$/sq ft
2" Classic Deco Frame	3-sided	(Width+4")	х	(Height+2")	/ 144	х	\$/sq ft
	2 sided with Sill Plate	(Width+4")	х	(Height+2")	/ 144	х	\$/sq ft
	2-sided	(Width+4")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+6")	х	(Height+6")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+6")	х	(Height+6")	/ 144	х	\$/sq ft
3" Ridge Deco Frame	3-sided	(Width+6")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+6")	х	(Height+3")	/ 144	х	\$/sq ft
	2-sided	(Width+6")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+5")	X	(Height+5")	/ 144	X	\$/sq ft
2.5" Mission deco frame	3-sided	(Width+5")	×	(Height+2.5")	<mark>/ 144</mark>	×	\$/sq ft
	2-sided	(Width+5")	×	(Height)	/ 144	×	\$/sq ft
	4-sided	(Width+4 ½")	х	(Height+4½")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+4 ½")	х	(Height+4½")	/ 144	х	\$/sq ft
3" Crown Z Frame	3-sided	(Width+4 ½")	х	(Height+21/4")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+4 ½")	х	(Height+21/4")	/ 144	х	\$/sq ft
	2-sided	(Width+4 1/2")	х	(Height)	/ 144	х	\$/sq ft

# Pricing


	4-sided	(Width+2 ½")	х	(Height+21/2")	/ 144	х	\$/sq ft
	3-sided with Sill Plate	(Width+2 1/2")	х	(Height+2½")	/ 144	х	\$/sq ft
2" Bel Air Z Frame 2" Bullnose Z Frame	3-sided	(Width+2 1/2")	х	(Height+11/4")	/ 144	х	\$/sq ft
	2-sided with Sill Plate	(Width+2 1/2")	х	(Height+11/4")	/ 144	х	\$/sq ft
	2-sided	(Width+2 1/2")	х	(Height)	/ 144	х	\$/sq ft
	4-sided	(Width+2")	х	(Height+2")	/ 144	х	\$/sq ft
1 1/2" Bullnose Z Frame	3-sided with Sill Plate (N/A w/ Tilt out Z)	(Width+2")	х	(Height+2")	/ 144	х	\$/sq ft
1 ¼ " Beaded Z Frame/ Bullnose Tilt Out Z Frame	3-sided	(Width+2")	х	(Height+1")	/ 144	х	\$/sq ft
Builnose Tilt Out 2 Frame	2-sided with Sill Plate (N/A w/ Tilt out Z)	(Width+2")	х	(Height+1")	/ 144	х	\$/sq ft
	2-sided	(Width+2")	х	(Height)	/ 144	х	\$/sq ft
	Inside	Width	х	Height	/ 144	х	\$/sq ft
Vintage Hang Strip	Outside 4-sided	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
Traditional Hang Strip	Outside 3-sided	(Width+3")	х	(Height+1½")	/ 144	х	\$/sq ft
	Outside 2-sided	(Width+3")	х	(Height)	/ 144	х	\$/sq ft
	Outside 4-sided	(Width+3")	х	(Height+3")	/ 144	х	\$/sq ft
Vintage L Frame/	Outside 3-sided	(Width+3")	х	(Height+1½")	/ 144	х	\$/sq ft
Beaded L Frame	Outside 2-sided	(Width+3")	х	(Height)	/ 144	х	\$/sq ft
Track Shutter**							
Inside and Semi-Inside Mount	Width	Х	Height	/144	Х	\$/sq ft	
Outside Mount	(Width+3")	х	(Height+3")	/144	х	\$/sq ft	

# **Appendix**


## Color Coordination Chart


Color ID	Color Name	New Hinge color (Default for non-Waterproof option)	New Ring pull color	New T post connector color	Top Track color (Default)	Hinge color (Default for Waterproof option)
001	Pure White	Pure White	White white	Pure White	White <b>White</b>	
002	Extra White	Silk White	White	Silk White	White	
003	Silk White	Silk White	White	Silk White	White	
<mark>004</mark>	<b>Bright White</b>	Silk White	White white	Silk White	White <b>White</b>	
006	Pearl Pearl	<u>Pearl</u>	<mark>Pearl</mark>	Pearl Pearl	White	
007	Ivory Lace	Bisque	Bisque	Bisque	White	
009	Creamy	Pearl	Pearl	Pearl	White	
012	Crisp Linen	Crisp Linen	Bisque	Bisque	White	
016	Butter	Crisp Linen	Bisque	Bisque	White	
019	String	String	Bisque	Bisque	White	
030	Moondust	Sea Mist	Brushed Nickel	Nickel Plated	Anodised Silver	
032	Sea Mist	Sea Mist	Brushed Nickel	Nickel Plated	Anodised Silver	
042	Hall Gray	Sea Mist	Brushed Nickel	Nickel Plated	Anodised Silver	
<mark>046</mark>	<mark>lce</mark>	Silk White	White white	Silk White	White	Stainless Steel
<mark>048</mark>	<u>Chai</u>	Nickel Plated	Brushed Nickel	Nickel Plated	Anodised Silver	Stainless Steel
049	Stone Gray	Stone Gray	Brushed Nickel	Nickel Plated	Anodised Silver	
051	Brown Gray	Brown Gray	Brushed Nickel	Nickel Plated	Anodised Silver	
<mark>053</mark>	Clay	Nickel Plated	Brushed Nickel	Nickel Plated	Anodised Silver	
<mark>063</mark>	<b>Decorators White</b>	Silk White	White White	Silk White	White white	
<mark>066</mark>	Winchester White 2010	Pearl Pearl	Pearl	Pearl Pearl	White	
<mark>073</mark>	Sky Gray	Silk White	White White	Silk White	Anodised Silver	
074	Element Gray	Sea Mist	Brushed Nickel	Nickel Plated	Anodised Silver	
075	Storm Gray	Sea Mist	Brushed Nickel	Nickel Plated	Anodised Silver	
<mark>077</mark>	Dawn	Silk White	White	Silk White	White	
<mark>078</mark>	Cloud Blue	Silk White	White	Silk White	White	
080	Taupe Gray	Taupe Gray	Brushed Nickel	Nickel Plated	Anodised Silver	
<mark>836</mark>	Classic Black	Black	Black	Black	Anodised Silver	


# Louver Depth Clearance




## Louver Depth Clearance for Specific Frames









#### New PerfectTilt RF (Not available for waterproof option)

The new PerfectTilt RF has many exciting features & benefits.

- iPhone and iPad control with hub (optional)
- Quick response to tilt commands
- 8 pre-programmed louver positions and one custom position with remote. Over 30 custom louver positions with Dial.
- Louvers can be tilted by hand, remote or app (via hub) without neither the need for flipping switches nor the risk of damage because of incorrect switch settings.
- Two long-lasting rechargeable 18650 Lithium-ion batteries per module unit last up to 1 year on a single charge via USB port
- High efficiency solar panel included for extending battery charge
- Water repellant module units
- Built-in jam protection for child and pet safety

# **Parts and Names:**



### Specifications:

Shutter Type	All types except bi-fold double hung or panel with gap at bottom over 0.1" (no				
Griditer Type	support on bottom)				
Specialty Shutter	All shapes except shapes without a vertical stile in the middle (for example,				
Shape	eyebrow, elongated eyebrow, half-round sunburst without horizontal louvers)				
Tilt System	Invisible Tilt only, the tilting system will not split unless specified				
Stile Width	2.25" stile only				
Louver	2.5", 3", 3.5", 4.5" Elliptical louver				
	Min. Panel Height				
		With Staggered motors			
	With lined up Motors	(which is default for 180 degree bifold track shutters;			
		and optional for other types of shutters)			
		Louver space not less than 26", so at least			
Panel Size Limit		13 louvers for 2.5" louver;			
Fanel Size Limit	18"	11 louvers for 3" louver;			
		9 louvers for 3.5" louver;			
		7 louvers for 4.5" louver.			
	Max. Panel Height without divider rail: 78"				
	Min. Panel Width Limit:8 11/16"				
	Max Width Limit: same as regular non-motorized shutters				


### Components:

Items	drawing
Norman Dial (Remote) and Docking: Dimensions: 68mm diameter x 34mm Distance of transmission (control): 100 meters without shelter	SET ALL A 1
Default color ring's color: black Optional color ring's colors: White, Gray, Brone, Red	
Module Model: PerfectTilt G4  Module color is White for shutter colors Pure White, Silk White & Pearl; Module color will be match shutter colors except Pure White, Silk White & Pearl.	Button Micro USB
Dimensions: 332.5 x 38.5 x 36.8 mm  One for each louver section,  2X long-lasting rechargeable 18650 lithium-ion batteries built-in, charge PerfectTilt G4 Module by Micro USB interface with 5V.1A power bank or adaptor.	
Micro USB cable (Optional) Color: White For charging PerfectTilt G4 Module.	

#### Slotted Point Driver

One for each louver section.

Connect the Easy Tilt and the Module; when fit the slotted point driver into the stile, make sure the angle is the same as that of the louvers.



#### Norman Hub

Color: Black

Dimensions: 94mm diameter x 27.8mm

Micro USB cable

Color: Black

Connect the Smart phone and the Norman hub, all shutters assigning to the remote can be controlled by APP via Norman hub.



### Note: It will be available in March 2019.

#### Repeater

Color: black


Plug Repeater into the enclosed Power Adapter and then plug into home power supply.

It is recommended to deploy each room with a repeater; If the distance is more than 10 meters, add one more repeater.



#### ♦ Frame Cut-Out

For single panel or configuration similar to single panel with frame, the module location will conflict with the light block of the frame, so there will be cut-out on the light block of the frame to stop the conflict, the length for the cut-out would be 335mm



#### Clearance:


The module will protrude 15.5mm (5/8") from the back of the stile, please allow 17mm (11/16") clearance for the module.



E.g.: Below is the situation **not available** for the module unless enough build-out is added to the frame

Hang Strip OM: beside the panels

When module is on the left/right most stiles, the protrusion part will conflict with the wall.




L Frame with light block thickness less than 3/4" OM:

When module is on the left/right most stiles, the protrusion part will conflict with the wall.




Side view for module in panel with different louver types




### For Motorized 90° Bifold Track Shutter:


- 1) Both 3" and 3.5" Header are available;
- 2) The L Shape Light Block will be cut out 1/4" to avoid the confliction with the module;



#### For Motorized 180° Bifold Track Shutter:

- 1) The default header width is 3.5"; The min. Header width is 3.25"; so for 3" header, 1/4" extension is required;
- 2) The L Shape Light Block will be cut out to avoid the confliction with the module; 0.2" extension is necessary for installation of the top and bottom pivots;






Module Location: (Easy Tilt will be on the same side as the module)

### For regular shutter and bi-fold Application (Except for bifold track):

1) Single Panel: Module will be on the un-hinge stile

2) 2 Panels: LL, LR, RR



3) 3 Panels: LLR/LRR




4) 4 Panels: LLRR




### For 90° Bifold Track:

### LL/RR



#### LLRR




### **Special Note on Bi-fold Configurations**

Please be aware that in bi-fold configurations, the motorization modules will touch each other when the panels are folded together, so the panels can't be able to stack together as tightly as that of the non-motorized shutters.

Additionally, before folding the bi-fold panels together, please ensure that the louvers are returned to a completely closed position (either up or down) to prevent louver damage when folding panels.


For better fold, it is optional to have the modules staggered for bi-fold.

However, for 180° bifold track shutter, the modules can only be staggered.




### For By-Pass Application


### 2 panels side open




### 3 panels center open (not available for Open Bypass)



### 4 panels center open



#### 4 panels side open




### For Special Shape Application:

Module location will be the same as the Invisible Tilt location.


### SHUTTER LOOK FROM FRONT AND BACK

The front side of the shutter

The back side of the shutter



- \* No Receiver / Louver Cap
- \* Invisible tilt only



\*The light block would be cut out along the module.