

RULE X

RACE CAR SPECIFICATIONS

I. CAR APPEARANCE

- A. All cars must pass a technical inspection by the Director of Competition or designated person before being allowed to race.
- B. All cars must present a neat appearance to the Promoter and the crowd.
- C. Pit crews must be in a presentable condition.
- D. Each car will be required to have a number prominently painted on the nose and each side of the tail. Duplicate numbers at any track may require the alteration of the number by adding a number or letter to the car.
- E. After a number is assigned to a particular car and owner, it will remain with the owner until the end of the racing season.

II. MIDGET SPECIFICATIONS

- A. Design and Construction: All phases of design and construction of any car are subject to the approval of the Technical Committee. The Stewards and Technical Committee may exclude any car, design, or construction which they have deemed dangerous.
- B. Car Size Limits: The wheelbase must be at least 66 inches, but not more than 76 inches with a maximum width of 65 inches.
- C. Car Construction
 - 1. All cars must be of the open wheel, open cockpit style.
 - 2. The engine must be covered with a cowling or hood and secured in place. The hold or cowling need not enclose the sides of the engine.
 - 3. The car must have a floorboard or under pan (extend from firewall to the front of the seat) that provides adequate protection to the Driver.
 - 4. Radiator catch tanks and under pan diapers may be required if warranted by track conditions.

5. The cockpit opening must be located directly behind the engine compartment.
6. Air foils, wings, spoilers, or other aerodynamic appendages will not be permitted. The Director of Competition may have any panel or part removed, which is his/her opinion is not within the spirit or intent of this rule.
7. Seats: No fiberglass or plastic seats will be allowed. A minimum of 4 mounts will be used (5/16 bolts with 2" washers). All seats must be of high back style.
8. Weight: All cars will weigh a minimum of 1035 pounds; including water, oil, fuel and the driver. Cars may be weighed prior to and/or following any event. Cars weighed at the completion of an event may not add fuel or ballast to satisfy the minimum weight requirement.
9. Roll Cage: All cars must be equipped with an integral roll cage that does not encroach upon an imaginary cylinder, 20" in diameter, extending upward from the cockpit opening. The roll cage should extend 4" above the top of the Driver's helmet when the Driver is sitting in an upright position. All cars constructed after January 1, 1997, should have roll cages and uprights constructed of 4130 1-3/8" 0.095 minimum specifications. All roll bars and/or cages must be so designed as to permit the lifting of the car in case of an accident. SFI roll cage padding highly recommended.
10. Water / Oil Coolers: No water or oil coolers are to be placed above or besides the cockpit opening.
11. Chassis Protrusions: Sharp chassis protrusions (grease fittings, cotter keys, etc.) must not be located in close proximity to the tires.
12. Bumpers and Nerf Bars: Cars must be equipped with adequate bumpers that are securely fastened to the structural components of the car. No titanium or aluminum allowed.
13. Axles: Front axles constructed of aluminum or titanium will not be permitted.
14. Steering Mechanism: The steering mechanism should be in accordance with sound engineering principles and subject to inspection. A quick release type steering wheel is required. No pin type quick release or plastic quick release will be allowed.
15. Brakes: Cars must be equipped with suitable brakes. No Carbon Fiber Brakes Allowed.
16. Tires and Wheels
 - a. Hoosier tires are required on all four corners; right rear must be an SP 3 Left rear must be a D12, front tires must be a D12 or D15.

- b. Tire measurement: Maximum tire measurement will be 12", measured from outside wall to outside wall except for the right rear tire; which will have a maximum measurement of 14" measured from outside wall to outside wall.
- c. Wheels: The rim diameter must be 13". The rim width shall not exceed 8" except for the right rear, which may be a maximum of 10". Cars powered by four cylinder horizontally-opposed, two valves per cylinder, intake and exhaust valves in-line and on the same axis, may use a right rear wheel with a maximum width of 12".
- d. All balancing lugs must be securely fastened.
- e. Tire Prep
 - i. Any solvents or chemicals applied in any way to a tire that alters the chemical makeup of the compound or have the effect of altering tire durometer or construction is prohibited. Any tire can be confiscated or sampled at any time. Penalties from tires found to deviate from the original factory benchmark specifications are as follows:
 - -First Offense: loss of points & forfeit purse for that event.
 - -Second Offense-Entrant/Driver 1-year suspension, loss of points & forfeit purse for that event, \$2,500.00 fin
 - ii. A tire protest is a \$500.00 fee to be paid to the competition director before the event. If tire samples are found illegal, the protest fee is returned. If tire sample is found legal, the protested entrant will receive a new tire replacement.
 - iii. Money won in an event may be held until the final determination is made by the independent laboratory.

17. Fuel System

- a. Fuel tanks must be constructed and supported in a manner that will insure every possible precaution has been taken to avoid rupture or breakage.
- b. Fuel tanks should not be altered by cutting out the bottom of lower tanks. Carbon fiber fuel tanks will not be allowed.
- c. Each car should be equipped with an approved bladder fuel tank.
- d. Fuel tanks must be within the body's contour.
- e. A flush-type cap is required on all exposed fuel caps.
- f. The fuel tank must have a check valve.

- g. Fuel systems must be equipped with a shut-off device located within easy reach of the Driver.
 - h. Fuel is restricted to methanol or ethanol.
 - i. All fuels are subject to testing at any time and any deviation or violation of these specifications will result in immediate disqualifications.
- 18. Firewall: An effective firewall of metal or approved fire retardant material must be installed between the engine compartment and the cockpit. It must be as leak proof as possible.
 - 19. Exhaust: Exhaust systems must be designed to create a minimum fire hazard and a minimum hazard to other competitors. Cars having exhaust pipes passing the cockpit in close proximity to the Driver must have raised metal pipes adjacent to the cockpit to afford protection to the Drivers and Mechanics.
 - 20. Mufflers: No carbon fiber mufflers will be allowed. Mufflers will only be mandatory at tracks that require them. Be prepared.
 - 21. Ignition: Kill switch must work and be within easy reach to the Driver.
 - 22. The use of carbon fiber or other composite material as a structural chassis component, torque tube, or as a suspension component is not allowed.
 - 23. No titanium front and rear axles, bumpers, or nerf bars will be allowed.
 - 24. Seat Belts: Must meet SFI 16.5 or SFI 16.1, be within manufacturer expiration label. (must have label) Seat belts must be installed and used in accordance with the manufacturer's instructions.

D. Safety Equipment:

- 1. Helmets: All Drivers participating in RMMRA sanctioned racing and/or speed events must wear safety helmets designed for this specific purpose and that meet the minimum requirements as prescribed by the Director of Competition. It is mandatory that all helmets have a Snell rating of SA 2005, SA 2010 or SFI 31.1. Helmets will be subject to inspection at each event by the Technical Committee. Only those considered in good condition and recent design and manufacture will be permitted.
- 2. A SFI approved head and neck restraint system is highly recommended.
- 3. Racing Uniforms: All Drivers must wear an approved one-piece racing uniform; complete with fire retardant head sock and/or skirt, socks, gloves, underwear, and shoes. Recommended all above items meet SFI Foundation Specifications 3.2A and 3.3

4. Arm Restraints – Arm restraints are mandatory and must be worn at all times during competition.
5. Steering Wheel Padding: The steering wheel hubs are highly recommended to be padded with resilient material of not less than $\frac{3}{4}$ " thickness.
6. Roll Cage Nets – If a car is not equipped with a full containment seat, it is highly recommended that the car be fitted with roll cage nets on both the left and right sides of the roll cage for all events. All roll cage nets must conform to SFI Specification 37.1, which specifies a functional quick release opening mechanism. Caution should be used when positioning head restraining nets to be certain that the driver's head cannot get under the net in case of an accident. The bottom of the roll cage net should be as close to the top of the shoulder as possible.
7. Roll Cage Padding – All chassis protrusions, roll cage tubes and roll bars in close proximity to the driver's helmet is highly recommended to be padded with a securely attached high impact material conforming to SFI Specification 45.1. This includes any vertical anti-intrusion supports alongside the driver.
8. Fire Equipment: The Entrant or Crew Chief of each car should have in his pit a fully charged five-pound powder fire extinguisher, or its

equivalent. A gauge or current inspection should be attached to each fire extinguisher.

E. Engines

1. **Pushrod Type Engines**

- a. Four cylinder in-line, two valves per cylinder, water cooled, with intake and exhaust ports on the same side of the head using an aluminum block and **approved** non-cross flow aluminum "Fontana" cylinder head.

Maximum of 179 CID (2934cc)

- b. Fontana (Rhino) sealed spec engine.

Maximum of 200 CID (3278cc)

- c. Four cylinder in-line, two valves per cylinder, water cooled utilizing an aluminum block and/or **approved** head.

Gaerte Block - Maximum of 177 CID (2900cc)

Mopar Block – Maximum of 171 CID (2803cc)

Toyota Engine – Maximum of 166 CID (2721cc)

- d. All other push rod engines, using billet block, Non-Gaerte or Non- Mopar blocks maximum of 166 CID (2721cc)

2. Single Overhead Camshaft Type Engines

- a. Four cylinder in-line, aluminum block and head, 2 valves per cylinder.

Maximum of 161CID (2639cc)

3. Double Overhead Camshaft Type Engines

- a. Honda K-Series four cylinder in-line, water cooled, four valves per cylinder, must use Honda OEM cylinder block and cylinder head.

Maximum of 154.6 CID (2533.5cc)

- b. The stock production "Cosworth Vega" four cylinders, in-line, four valves per cylinder, utilizing the stock production block and head. Alteration of the basic design of the head or block is prohibited. Maximum 127 CID (2082 cc).

- c. Ecotec four cylinders, in-line, four valves per cylinder. Maximum 146 CID (2400cc).

4. Complete engines and/or major components must be available in a reasonably sufficient supply to all competitors at comparative prices.

5. All engines must be normally aspirated, internal combustion, four cycle, reciprocating piston type, incorporating a maximum of four cylinders. Only one spark plug per cylinder will be allowed. Camshaft timing must be fixed. Any device used to alter camshaft timing during engine operation is prohibited. Sever penalties will be issued to the entrant and engine builder if such devices are found. EXCEPTION – Production block and head engines under 146 CID.
6. The preceding engine sized is maximum permitted. No clean up allowed.
7. RMMRA. Reserves the right to disallow any engine for competition, which in its judgment does not meet the spirit and intent of competitive racing, in regards to cost and/or performance. Any engines not covered by the preceding specifications must be submitted for approval prior to entering the competition.
8. Unapproved engines may be run under observation prior to amending the rulebook with the approval of the Director of Competition.
9. All chain driven cars and engines are prohibited

F. Miscellaneous

1. The use of in-car radio transmitting devices is prohibited.
2. Only one-way communication from RMMRA Race Control will be allowed and is mandatory.
3. The use of electronic logic processor to control any function of the race car is prohibited. (Note: This rule does not include electronic ignition and/or electronic tachometers).
4. The use of electronic logic processors of any type to control any function of the race car and/or any system for gathering continuous data from any function of the race car is strictly prohibited for acceptance of ignition.

III. MEMBERSHIP REQUIREMENTS

- A. No person shall be discriminated against because of sex, race, religion, or national origin.
- B. Levels of Membership are as follows:
 1. Full Membership: Will earn RMMRA championship points, be eligible for any contingency awards if all requirements are met and have coverage under the secondary insurance plan (except for Associate Membership, which is a non-competition membership).
 2. Temporary Permit: Will be required for non-RMMRA member entrants for any RMMRA sanctioned race. A temporary permit holder is not eligible for any RMMRA championship points or any contingency awards and will not be covered by the secondary insurance plan.

RULE XI

POINT SYSTEM AND AWARDS

- 1101. Awards:** The RMMRA shall celebrate performance worthy of weekly and/or annual recognition by the presentation of an award and/or trophy, based on point standing or number of wins, and shall recognize special performance and contribution to the sport with standing awards based on nomination and selection by the Club.
- 1102. Competition Awards:** Competition awards may be made for individual events and cumulatively at season end in the following categories:
1. The Time Trails shall be awarded to the driver setting quick-time the most times during the season.
 2. The Trophy Dash Award shall be awarded to the driver winning the event the most times in a season.
 3. The Main Event Award shall be awarded to the driver winning the event the most times in season
 4. The Championship Car, the Championship Driver, and the Championship Mechanic Awards shall be awarded on the basis of the most points accumulated in a season.
- 1103. Awards by Vote:** Awards by vote may be made annually in the following categories.
1. These awards shall be presented to the persons selected in an election by written ballot of eligible car owners and drivers (member owners and drivers who participated in at least 30 percent of the races for that season).
 - A. Sportsmanship
 - B. Mechanic of the Year
 - C. Rookie of the Year, with and without experience.
 - D. Best Looking Car
 - E. Best Looking Crew
 - F. Most Improved Driver
 2. Significant contribution to Midget auto racing in the preceding year. This award is selected by the RMMRA Board of Directors.
- 1104. Point System:** A point system shall be used to determine weekly point standings and the winners of Championship Car, Driver, and Mechanic Awards, defined as follows:

1. Points for a position in the various events shall be awarded according to a schedule approved by the Board of Directors and published by the Secretary.
2. The point schedule shall include the following events:
 - A. Time Trails
 - B. Heat Races
 - C. Semi–Main
 - D. Main Event
3. Points for Heat Races will be awarded only for those Heat Races qualified for in time trials or original draw, not for heat races for winners and losers.
4. Cars and drivers earning points in both Semi–Main and Main Events shall receive the greater number of points earned in either event, but not for both events.
5. Registered RMMRA drivers will earn and be awarded driver points in RMMRA point races, whether or not the car has been registered with RMMRA or entered in the particular race event.
6. **Any car/driver unable to start and compete in the feature event will NOT receive feature points.**
7. **See current addendum for points schedule.**

1105. Ties: It shall be the responsibility of the Board of Directors to resolve any ties in awards that may develop.

1106. Monetary Awards: Money awards for individual events (**Purses**) shall be made according to finish order in a Schedule set or negotiated by the President and approved by the Board of Directors.

1. *Payment shall be made by check, and mailed to, the Car Owner's address of record. Such payment shall be made prior to the next event whenever possible.*
2. When time or circumstance does not permit mailing, payment may be at the next event, or at the conclusion of the current event.
3. If payment is made in cash, it will only be delivered to the Car Owner or a representative designated by the Owner in writing, with cash receipt signed for by Owner or representative.
4. The Schedule of purse amounts shall be posted by the President prior to event.

ADENDA

ROCKY MOUNTAIN MIDGET RACING ASSOCIATION 2025

Membership Fees

TYPE OF MEMBERSHIP:	Before April 15	After April 15
Associate Member (club supporter)	\$25.00	\$25.00
Participating Member (voting)	\$40.00	\$40.00
Owner/Driver	\$300.00	\$325.00
Owner	\$137.00	\$162.00
Driver	\$163.00	\$188.00
Additional Car Number _____	\$50.00	\$50.00
Additional Car Number _____	\$50.00	\$50.00
Supplemental medical insurance for non-driver	\$105.00	\$105.00
Guest Fee – one night		\$50.00

* Mandatory Insurance for all RMMRA Drivers, is included in amounts shown

New memberships, which include insurance, may change during season, if premiums change.

Cars and/or Drivers will not be allowed to compete until Membership fees are paid in full. See prior for Guest privileges.

RMMRA POINTS SCHEDULE

POS	QUALIFYING	HEAT RACE	SEMI MAIN	FEATURE
1	5	20		50
2	4	18		45
3	3	16		42
4	2	14		40
5	1	12	6	38
6	1	10	5	36
7	1	8	4	34
8	1	6	3	32
9	1	4	2	30
10	1	2	1	28
11	1		1	26
12	1		1	24
13	1			22
14	1			20
15	1			18
16	1			16
17	1			14
18	1			12
19	1			10
20	1			8
21	1			
22	1			
23	1			
24	1			
25	1			
26	1			
27	1			
28	1			
29	1			
30	1			
31	1			
32	1			

1 ALL BELOW

NOTES

When more than 12 cars are qualified for semi-main competition after heats, two semis should be run for equal points. Time and track circumstances may require adjustment.

Cars and drivers earn points either for feature or semi (largest number), but not both.

